

Title (en)

CONTROL ARRANGEMENT AND METHOD FOR CONTROLLING AN EXHAUST VALVE

Title (de)

STEUERANORDNUNG UND VERFAHREN ZUR STEUERUNG EINES AUSLASSVENTILS

Title (fr)

AGENCEMENT DE COMMANDE ET PROCÉDÉ DE COMMANDE D'UNE SOUPAPE D'ÉCHAPPEMENT

Publication

EP 2941546 A1 20151111 (EN)

Application

EP 14700516 A 20140103

Priority

- FI 20135017 A 20130107
- FI 2014050002 W 20140103

Abstract (en)

[origin: WO2014106688A1] The control arrangement and method allow an additional opening of a cam-driven exhaust valve (17) of an internal combustion engine for exhaust gas recirculation. Hydraulic fluid can be introduced into a hydraulic fluid chamber (11) that is arranged between a cam (2) and force transmission means (12, 18) and delimited by a piston (5) that is engaged with the force transmission means (12, 18) at least during the opening and closing movement of the exhaust valve (17). The cam (2) comprises a portion (2c) below the base circle (2a) of the cam (2), and engagement of a cam follower wheel (3) with the portion (2c) below the base circle (2a) is arranged to prevent outflow from the hydraulic fluid chamber (11).

IPC 8 full level

F01L 9/12 (2021.01); **F01L 13/00** (2006.01); **F01L 13/08** (2006.01)

CPC (source: EP FI)

F01L 1/24 (2013.01 - FI); **F01L 9/12** (2021.01 - EP); **F01L 13/0031** (2013.01 - EP FI); **F01L 13/08** (2013.01 - EP); **F02D 13/0242** (2013.01 - FI)

Citation (search report)

See references of WO 2014106688A1

Cited by

WO2018166612A1; WO2024013634A1; EP3596317B1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2014106688 A1 20140710; EP 2941546 A1 20151111; EP 2941546 B1 20161221; FI 124813 B 20150130; FI 20135017 A 20140708

DOCDB simple family (application)

FI 2014050002 W 20140103; EP 14700516 A 20140103; FI 20135017 A 20130107