

Title (en)

SLIDING CONTACT WEAR SURFACES COATED WITH PTFE/ALUMINUM OXIDE THERMAL SPRAY COATING

Title (de)

MIT EINER PTFE-/ALUMINIUMOXID-WÄRMESPRÜHBESCHICHTUNG BESCHICHTETE GLEITKONTAKTVERSCHLEISSFLÄCHEN

Title (fr)

SURFACES D'USURE À CONTACT GLISSANT REVÊTUES D'UN REVÊTEMENT PAR PULVÉRISATION THERMIQUE DE PTFE/D'OXYDE D'ALUMINIUM

Publication

**EP 2961859 A2 20160106 (EN)**

Application

**EP 13876138 A 20131106**

Priority

- US 201361769587 P 20130226
- US 2013068708 W 20131106

Abstract (en)

[origin: WO2014133602A2] A method of applying a wear-resistant coating to aluminum sliding contact wear surfaces is disclosed. The method includes providing a plurality of parts having sliding contact wear surfaces and thermal spray coating at least one of a composite aluminum oxide and PTFE or a blend of aluminum oxide and PTFE. The disclosed method may be used to repair aluminum parts subject to sliding contact wear as well as in the design of new aluminum parts subject to sliding contact wear. Improved compressor bleed valves for gas turbine engines and improved fan exit case assemblies are also disclosed.

IPC 8 full level

**C23C 4/04** (2006.01); **C23C 24/04** (2006.01)

CPC (source: EP US)

**C23C 4/04** (2013.01 - EP US); **C23C 4/11** (2016.01 - EP US); **C23C 24/04** (2013.01 - EP US); **F02C 9/18** (2013.01 - US); **F04D 27/0215** (2013.01 - EP US); **F04D 27/023** (2013.01 - EP US); **F04D 29/023** (2013.01 - EP); **F05D 2300/2112** (2013.01 - EP US); **F05D 2300/432** (2013.01 - EP US); **F05D 2300/603** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**WO 2014133602 A2 20140904**; **WO 2014133602 A3 20141023**; EP 2961859 A2 20160106; EP 2961859 A4 20161102; EP 2961859 B1 20180919; US 10683808 B2 20200616; US 2015369133 A1 20151224

DOCDB simple family (application)

**US 2013068708 W 20131106**; EP 13876138 A 20131106; US 201314758742 A 20131106