

Title (en)

PREVENTION OF WIRELINE DAMAGE AT A DOWNHOLE WINDOW

Title (de)

VORBEUGUNG VON DRAHTLEITUNGSSCHÄDEN AN EINEM BOHRLOCHFENSTER

Title (fr)

PROCÉDÉ POUR PRÉVENIR DES DOMMAGES OCCASIONNÉS À UN CÂBLE DANS UNE FENÊTRE DE FOND DE TROU

Publication

EP 2971459 A2 20160120 (EN)

Application

EP 14719166 A 20140314

Priority

- US 201361784784 P 20130314
- US 2014028508 W 20140314

Abstract (en)

[origin: US2014262334A1] A bottom hole assembly (BHA) which is transported via a wireline through downhole and lateral wellbores and thence through a wellbore window aperture, the BHA carrying with it a blocking tool which is adapted to engage the edge of a lateral wellbore window and prevent the wireline from contacting and abrading against that edge of the window, the blocking tool being detachable from the BHA which proceeds axially distally through the wellbore window while the wireline slides through the blocking tool. Upon withdrawal of the BHA the blocking tool is reattached thereto and is removed with it.

IPC 8 full level

E21B 23/14 (2006.01)

CPC (source: EP US)

E21B 23/14 (2013.01 - EP US); **E21B 41/0035** (2013.01 - EP US)

Citation (search report)

See references of WO 2014152979A2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

US 2014262334 A1 20140918; CA 2905494 A1 20140925; CN 105408579 A 20160316; EP 2971459 A2 20160120; WO 2014152979 A2 20140925; WO 2014152979 A3 20150205

DOCDB simple family (application)

US 201414211677 A 20140314; CA 2905494 A 20140314; CN 201480027565 A 20140314; EP 14719166 A 20140314; US 2014028508 W 20140314