

Title (en)

APPARATUS AND METHOD FOR COMMINUTION OF ORE WITH RECIRCULATION

Title (de)

VORRICHTUNG UND VERFAHREN ZUM ERZZERKLEINERN MIT RÜCKFÜHRUNG

Title (fr)

APPAREIL ET PROCÉDÉ POUR LE BROYAGE DE MINERAIS AVEC RECIRCULATION

Publication

EP 2981361 B1 20180829 (DE)

Application

EP 14715322 A 20140407

Priority

- DE 102013005931 A 20130405
- EP 2014056904 W 20140407

Abstract (en)

[origin: CA2910741A1] The invention relates to a device (290) for comminuting ore and/or slag, comprising an ore feeding unit (1) for feeding ore which is to be comminuted to a first pulverizer, the first pulverizer (300) being composed of at least two comminuting elements (30, 40) which can be moved relative to each other, said elements forming together at least one comminuting space for the ore which is to be comminuted such that, by a relative movement in the form of a rotation about the rotational axis of at least one of the two comminuting elements (30, 40), the ore which is to be comminuted is at least partially pulverized. One or more accelerating elements (35), in particular protrusions (35), are provided on at least one of the comminuting elements (30, 40), said accelerating elements being arranged in particular on the end face of at least one of the two comminuting elements (30, 40) and accelerating and comminuting the ore to be comminuted by the rotation of one of the two comminuting elements (30, 40). An intermediate space (60) is provided between the two comminuting elements (30, 40) and/or in at least one of the two comminuting elements, through which space the pulverized ore, during the rotation, is transported from the center of rotation toward the outside and away from the two comminuting elements (30, 40). The claimed invention also comprises an outlet device (14) for discharging the pulverized ore through the first pulverizer which is connected to the intermediate space (60). The outlet device is connected to a separating device (413) through which the pulverised ore can be distributed in two parts, the first part of the pulverised ore having a particle size which is essentially larger than a predetermined particle size of the second part of the pulverised ore, the first part of the pulverised ore being guided to the first pulverizer or to the second pulverizer and the second part of the pulverised ore is guided to a flotation device.

IPC 8 full level

B02C 7/06 (2006.01); **B02C 7/11** (2006.01); **B02C 15/06** (2006.01); **B02C 19/00** (2006.01); **B02C 21/02** (2006.01); **B02C 23/12** (2006.01)

CPC (source: EP US)

B02C 7/06 (2013.01 - EP US); **B02C 7/11** (2013.01 - EP US); **B02C 15/06** (2013.01 - EP US); **B02C 19/0012** (2013.01 - EP US);
B02C 21/02 (2013.01 - EP US); **B02C 23/12** (2013.01 - EP US); **B02C 23/38** (2013.01 - US)

Cited by

CN107029827A

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102013005931 A1 20141009; AU 2014247021 A1 20151119; AU 2014247021 B2 20180628; CA 2910741 A1 20141009;
CL 2015002954 A1 20160624; CN 105408024 A 20160316; CN 105408024 B 20180202; EP 2981361 A1 20160210; EP 2981361 B1 20180829;
US 10556237 B2 20200211; US 2016136653 A1 20160519; WO 2014162012 A1 20141009; ZA 201507357 B 20170329

DOCDB simple family (application)

DE 102013005931 A 20130405; AU 2014247021 A 20140407; CA 2910741 A 20140407; CL 2015002954 A 20151005;
CN 201480030929 A 20140407; EP 14715322 A 20140407; EP 2014056904 W 20140407; US 201414782360 A 20140407;
ZA 201507357 A 20151005