

Title (en)
LOCATION POINTING DEVICE

Title (de)
POSITIONSEINGABEVORRICHTUNG

Title (fr)
DISPOSITIF DE POINTAGE D'EMPLACEMENT

Publication
EP 2998832 B1 20170809 (EN)

Application
EP 14818760 A 20140520

Priority
• JP 2013134721 A 20130627
• JP 2014063293 W 20140520

Abstract (en)
[origin: EP2998832A1] An object of the present invention is to realize thinning of a casing of a position indicator while preventing degradation in signals transmitted and received to and from a sensor of a position detecting device. The position indicator includes a columnar magnetic core provided within a cylindrical casing with an axial direction of the casing as a direction of a central axis of the magnetic core. A coil is wound so as to have the central axis of the columnar magnetic core as a center. A core body is provided so as to have a tip portion exposed to an outside from an opening formed on one end side in the axial direction of the cylindrical casing. The magnetic core has a flat cross-sectional shape, and has a tapered portion formed on a side of the tip portion of the core body in the direction of the central axis of the magnetic core, the tapered portion being tapered off toward the tip portion of the core body.

IPC 8 full level
G06F 3/0354 (2013.01); **G06F 3/046** (2006.01)

CPC (source: EP US)
G06F 3/03 (2013.01 - US); **G06F 3/03545** (2013.01 - EP US); **G06F 3/046** (2013.01 - EP US); **G06F 2203/04103** (2013.01 - US)

Cited by
JPWO2016208476A1; US10296113B2

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2998832 A1 20160323; **EP 2998832 A4 20160511**; **EP 2998832 B1 20170809**; CN 104903822 A 20150909; CN 104903822 B 20170623; JP 2015011428 A 20150119; JP 5647715 B1 20150107; KR 101682324 B1 20161205; KR 20160011177 A 20160129; TW 201500983 A 20150101; TW I614641 B 20180211; US 2016162049 A1 20160609; US 9600095 B2 20170321; WO 2014208219 A1 20141231

DOCDB simple family (application)
EP 14818760 A 20140520; CN 201480004010 A 20140520; JP 2013134721 A 20130627; JP 2014063293 W 20140520; KR 20157018898 A 20140520; TW 103116080 A 20140506; US 201414648233 A 20140520