

Title (en)

METHOD FOR OPERATING A WASHING MACHINE ACHIEVING AN IMPROVED RESIDUAL MOISTURE CONTENT OF THE LAUNDRY, AND WASHING MACHINE SUITABLE THEREFOR

Title (de)

VERFAHREN ZUM BETRIEB EINER WASCHMASCHINE MIT EINER VERBESSERTEM RESTFEUCHTE DER WÄSCHE SOWIE HIERZU GEEIGNETE WASCHMASCHINE

Title (fr)

PROCÉDÉ DE FONCTIONNEMENT D'UNE MACHINE À LAVER À HUMIDITÉ RÉSIDUELLE DU LINGE AMÉLIORÉE ET MACHINE À LAVER ADAPTÉE DANS CE BUT

Publication

EP 3004448 A1 20160413 (DE)

Application

EP 14727436 A 20140519

Priority

- DE 102013210129 A 20130529
- EP 2014060217 W 20140519

Abstract (en)

[origin: WO2014191248A1] The invention relates to a method for rinsing laundry (7) in a washing machine having a control device (12) for controlling a program sequence, a drum (2), which is rotatably mounted in a liquor container (1), a heating device (13), a pump (16) and a drive motor (14) for the drum (2), according to which method, in a rinsing phase having one or more rinsing steps following a washing phase, at least in the last rinsing step after the last portion of rinsing water is added to the liquor container (1) and the laundry (7) is rinsed through, (a) the pump (16) is switched on and a free detergent solution (6) situated in the liquor container (1) is pumped out; (b) the pump (16) is then switched off and the drum (2) is operated at a spin speed ω_1 with the pump (16) switched off in order to reduce the moisture content of the damp laundry (7) from step (a) and to collect the water driven out in the process in the liquor container (1), such that for the quantity of water q in the liquor container, $q = q_{col}$; (c) if the quantity of water collected in step (b) is $q_{col} < q_{set}$, the liquor container (1) is filled up with water from the water supply (8, 9) until $q \geq q_{set}$ for the quantity of water q in the liquor container (1); (d) the quantity of water q in the liquor container (1) is heated to a predefined temperature T_{set} ; (e) the heated water from step (d) is distributed in the laundry (7); and (f) the drum (2) is operated at a spin speed ω_2 in order to drive heated water distributed in the laundry (7) from step (e) out of the laundry (7) and pump it away. The invention further relates to a washing machine suitable for carrying out the method.

IPC 8 full level

D06F 35/00 (2006.01); **D06F 33/32** (2020.01); **D06F 39/04** (2006.01); **D06F 39/08** (2006.01); **D06F 33/40** (2020.01)

CPC (source: EP RU US)

D06F 33/32 (2020.02 - EP RU US); **D06F 33/40** (2020.02 - EP RU US); **D06F 39/04** (2013.01 - EP RU US); **D06F 39/085** (2013.01 - EP RU US);
D06F 2103/04 (2020.02 - EP RU US); **D06F 2103/16** (2020.02 - EP RU US); **D06F 2103/18** (2020.02 - EP RU US);
D06F 2103/28 (2020.02 - EP RU US); **D06F 2105/02** (2020.02 - EP RU US); **D06F 2105/06** (2020.02 - EP RU US);
D06F 2105/08 (2020.02 - EP RU US); **D06F 2105/28** (2020.02 - EP RU US); **D06F 2105/48** (2020.02 - EP RU US)

Citation (search report)

See references of WO 2014191248A1

Cited by

EP3951042A4; US11028527B2; US11692300B2; US12060674B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102013210129 A1 20141204; CN 105283597 A 20160127; CN 105283597 B 20170711; EP 3004448 A1 20160413;
EP 3004448 B1 20170712; PL 3004448 T3 20171229; RU 2015152585 A 20170704; RU 2634578 C2 20171031; WO 2014191248 A1 20141204

DOCDB simple family (application)

DE 102013210129 A 20130529; CN 201480030514 A 20140519; EP 14727436 A 20140519; EP 2014060217 W 20140519;
PL 14727436 T 20140519; RU 2015152585 A 20140519