

Title (en)

Valve arrangement with improved failsafe operation

Title (de)

Ventilanordnung mit verbessertem ausfallsicherem Betrieb

Title (fr)

Agencement de soupape présentant un meilleur fonctionnement à sécurité intégrée

Publication

**EP 3012483 B1 20190213 (EN)**

Application

**EP 14189715 A 20141021**

Priority

EP 14189715 A 20141021

Abstract (en)

[origin: EP3012483A1] The present relates to a valve arrangement (1) for controlling a flow of damping medium in a shock absorber. The invention is based on the insight that traditional radial or angled fail safe flows create turbulence which affects the axial position of the control valve member by direct axial forces and increased friction due to radial forces acting on the control valve member. By instead providing a radial column (18) with an axial failsafe flow (20), the fail safe flow (20) is not dependent on the exact axial position of the control valve member (5) for creating the fail safe restriction, and moreover less turbulence arise affecting the axial position of the control valve member (5). Thereby an improved valve arrangement (1) is provided which has a more stable and reliable failsafe operation, resulting in a more dependable valve arrangement (1).

IPC 8 full level

**F16F 9/46** (2006.01)

CPC (source: CN EP US)

**F16F 9/34** (2013.01 - US); **F16F 9/465** (2013.01 - CN EP US); **F16F 9/466** (2013.01 - CN EP US); **F16K 31/0686** (2013.01 - US);  
**F16F 2230/24** (2013.01 - CN EP US)

Cited by

EP4063688A1; WO2023117961A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 3012483 A1 20160427; EP 3012483 B1 20190213;** CN 107076246 A 20170818; CN 107076246 B 20190924; JP 2017533387 A 20171109;  
JP 6668342 B2 20200318; US 10240656 B2 20190326; US 2017234395 A1 20170817; WO 2016062573 A1 20160428

DOCDB simple family (application)

**EP 14189715 A 20141021;** CN 201580056236 A 20151012; EP 2015073585 W 20151012; JP 2017520312 A 20151012;  
US 201515519522 A 20151012