

Title (en)  
CANNULA

Title (de)  
KANÜLE

Title (fr)  
CANULE

Publication  
**EP 3053552 B1 20180530 (EN)**

Application  
**EP 14848415 A 20140924**

Priority  
• JP 2013203399 A 20130930  
• JP 2014075177 W 20140924

Abstract (en)  
[origin: EP3053552A1] There is provided a cannula that is capable of controlling itself from easily slipping out from an eyeball when a surgical tool or the like is moved, does not damage the eyeball even when the base of the cannula and the eyeball make contact, and controls a pipe from detaching from the base. The cannula (10) is pierced through the eyeball in ophthalmic operations and includes a metal pipe (11) for piercing through the eyeball A; and a base (12) joined to an end side of the pipe and made of a material having flexibility. Moreover, the center part of an eyeball side end surface of the base should be depressed, and the shape of the contact portion of the base should be changed when the base makes contact with the eyeball.

IPC 8 full level  
**A61B 17/34** (2006.01); **A61F 9/007** (2006.01)

CPC (source: EP US)  
**A61B 17/3421** (2013.01 - EP US); **A61F 9/007** (2013.01 - EP US); **A61B 2017/3492** (2013.01 - EP US); **A61B 2090/036** (2016.02 - EP US)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 3053552 A1 20160810; EP 3053552 A4 20170517; EP 3053552 B1 20180530**; ES 2673598 T3 20180625; JP 2015066199 A 20150413; JP 6324013 B2 20180516; US 2016213511 A1 20160728; WO 2015046192 A1 20150402

DOCDB simple family (application)  
**EP 14848415 A 20140924**; ES 14848415 T 20140924; JP 2013203399 A 20130930; JP 2014075177 W 20140924; US 201415025360 A 20140924