

Title (en)  
Shaft and lifter for compression release

Title (de)  
Welle und Stößel zur Dekompression

Title (fr)  
Arbre et poussoir pour décompression

Publication  
**EP 3061930 B1 20181226 (EN)**

Application  
**EP 16155219 A 20160211**

Priority  
GB 201503074 A 20150224

Abstract (en)  
[origin: EP3061930A1] A camshaft (2) comprising a decompression device (1) to reduce pressure in a cylinder when an engine starts, the camshaft (2) having first and second lobes (14, 15) for actuating cylinder valves (62). The decompression device (1) has a shaft (10) located axially within the camshaft (2), and rotatable relative to the camshaft (2) to extend or retract a first and a second lifter (12, 13) radially. The first and second lifters (12, 13) are respectively provided inwardly of lobe faces of the first and second lobes (14, 15) on the camshaft (2) in a radial direction of the camshaft (2) such that the first lifter and the second lifter (12, 13) can extend outwardly or retract inwardly in the radial direction from the lobe faces. The shaft (10) has first and second eccentric portions (10A, 10B) located in transverse slots (12B, 13B) in the first and second lifters (12, 13) to extend or retract the first and second lifters (12, 13) respectively. The second lifter (13) has a longitudinal cut-out (13C) extending to the transverse slot (13B) of the second lifter (13) to allow the second eccentric portion (10B) to enter the transverse slot (13B).

IPC 8 full level  
**F01L 13/08** (2006.01)

CPC (source: EP)  
**F01L 13/085** (2013.01); **F01L 1/053** (2013.01); **F01L 2001/0473** (2013.01); **F01L 2250/02** (2013.01)

Cited by  
EP3523513B1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 3061930 A1 20160831; EP 3061930 B1 20181226; GB 201503074 D0 20150408**

DOCDB simple family (application)  
**EP 16155219 A 20160211; GB 201503074 A 20150224**