

Title (en)

SCREW FOR AVOIDING CRACKS AND BURRS

Title (de)

SCHRAUBE ZUR VERMEIDUNG VON RISSEN UND GRATEN

Title (fr)

VIS POUR ÉVITER FISSURES ET BAVURES

Publication

EP 3067575 B1 20220810 (EN)

Application

EP 15193537 A 20151106

Priority

TW 104107855 A 20150311

Abstract (en)

[origin: EP3067575A1] A screw according to the present disclosure includes a head (210), a shank (220), a thread (230), a plurality of first ribs (252) and at least one second rib (262). The thread is formed on the shank. The head is formed at one end of the shank and is configured to receive a fastening tool. The head is of tapered shape and has tapered side-surfaces, which include a first side surface (250) and a second side surface (260). The second side surface is located between the first side surface and the shank. The first ribs (252) are positioned on the first side surface (250). The second rib (262) is positioned on the second side surface (260).

IPC 8 full level

F16B 35/06 (2006.01)

CPC (source: EP US)

F16B 35/065 (2013.01 - EP US)

Cited by

CN110792670A; SE541064C2; EP4353979A1; EP3550160A1; US11835077B2; WO2020125890A1; US11879491B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3067575 A1 20160914; EP 3067575 B1 20220810; CA 2912846 A1 20160911; CA 2912846 C 20170919; CA 2912846 E 20160911;
CN 105972022 A 20160928; CN 105972022 B 20171219; DK 3067575 T3 20221114; ES 2929551 T3 20221130; JP 2016169859 A 20160923;
JP 6261552 B2 20180117; PL 3067575 T3 20221212; TW 201632744 A 20160916; US 10054148 B2 20180821; US 2016265578 A1 20160915

DOCDB simple family (application)

EP 15193537 A 20151106; CA 2912846 A 20151123; CN 201510414180 A 20150715; DK 15193537 T 20151106; ES 15193537 T 20151106;
JP 2015226185 A 20151119; PL 15193537 T 20151106; TW 104107855 A 20150311; US 201514927637 A 20151030