

Title (en)  
HEAT PUMP LAUNDRY DRYER

Title (de)  
WÄRMEPUMPENWÄSCHETROCKNER

Title (fr)  
SÈCHE-LINGE À POMPE À CHALEUR

Publication  
**EP 3068940 B1 20210901 (EN)**

Application  
**EP 13789362 A 20131113**

Priority  
EP 2013073722 W 20131113

Abstract (en)  
[origin: WO2015070901A1] The invention relates to a laundry dryer (1) comprising: a casing (2) supporting a drying chamber (3) for receiving a load to be dried; a process air conduit (11) in communication with the drying chamber (3) where a process air stream is apt to flow, a heat pump (30) having a heat pump circuit in which a refrigerant (R) can flow, said heat pump circuit including a first heat exchanger (31) where the refrigerant is cooled off and the process air stream is heated up, and a second heat exchanger (32) where the refrigerant is heated up and the process air is cooled off; said first and/or second heat exchanger being thermally coupled to the process air conduit (11) to perform heat exchange between said refrigerant flowing in said heat pump circuit and said process air stream; said first and/or second heat exchanger (31;32) further comprising a first (10) and a second heat exchanger module (10'), each module (10; 10') including an inlet header (5; 5') to direct a flow of said refrigerant (R) into said module (10, 10'); an outlet header (6; 6') to discharge said refrigerant (R) from said module (10, 10'); and a plurality of heat exchange layers (8; 8') fluidly connecting said inlet (5; 5') to said outlet header (6; 6') to enable said refrigerant (R) to flow from said inlet to said outlet header and/or vice versa; said layers (8; 8') being stacked one above the others in a predetermined stacking direction (Z; Z') and each layer (8; 8') including a plurality of channels (7); wherein said first and said second heat exchanger modules (10,10') are mounted adjacent one to the other and a first heat exchange layer (8) of the first module (10) and a second heat exchange layer (8') of the second module (10) are separated by a gap (g) in a direction incident to said stacking direction (Z, Z'), said first and said second heat exchanger modules (10, 10') including a plurality of fins (50) arranged on both said first and said second heat exchange layers (8, 8') and extending through said gap (g).

IPC 8 full level  
**D06F 58/20** (2006.01); **D06F 58/24** (2006.01); **F28D 1/053** (2006.01)

CPC (source: EP US)  
**D06F 58/206** (2013.01 - EP US); **D06F 58/24** (2013.01 - EP US); **F28D 1/0426** (2013.01 - EP); **F28D 1/0478** (2013.01 - EP); **F28D 1/05391** (2013.01 - EP); **F28D 2021/0038** (2013.01 - EP)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**WO 2015070901 A1 20150521**; AU 2013405474 B2 20190103; CN 105658866 A 20160608; CN 105658866 B 20180626; EP 3068940 A1 20160921; EP 3068940 B1 20210901; PL 3068940 T3 20220124

DOCDB simple family (application)  
**EP 2013073722 W 20131113**; AU 2013405474 A 20131113; CN 201380080349 A 20131113; EP 13789362 A 20131113; PL 13789362 T 20131113