

Title (en)
COMPRESSOR SYSTEM FOR A RAIL VEHICLE AND METHOD FOR OPERATING THE COMPRESSOR SYSTEM WITH SAFE EMERGENCY OPERATION

Title (de)
KOMPRESSORSYSTEM FÜR EIN SCHIENENFAHRZEUGS UND VERFAHREN ZUM BETRIEB DES KOMPRESSORSYSTEMS MIT EINEM SICHEREN NOTLAUFBETRIEB

Title (fr)
SYSTÈME DE COMPRESSEUR DESTINÉ À UN VÉHICULE FERROVIAIRE ET PROCÉDÉ PERMETTANT DE FAIRE FONCTIONNER LE SYSTÈME DE COMPRESSEUR DANS UN MODE D'URGENCE FIABLE

Publication
EP 3077673 A1 20161012 (DE)

Application
EP 14808924 A 20141202

Priority
• DE 102013113557 A 20131205
• EP 2014076166 W 20141202

Abstract (en)
[origin: WO2015082432A1] The invention relates to a compressor system for a rail vehicle, comprising a compressor (3), driven by an electrical machine (1) via a drive shaft (2), for producing compressed air for at least one compressed air tank (4), wherein the electrical machine (1) can be activated at least indirectly via a control device (5) for operating the electrical machine (1) at at least one nominal speed (n) between a maximum speed (m) and a minimum speed (i), wherein furthermore at least one pressure sensor (7) for determining the pressure for the control device (5) is disposed in a compressed-air-carrying line (6) downstream of the compressor (3). According to the invention, a final control element (8) for continuously influencing the speed of the electrical machine (1) is disposed between an electrical supply (15) and the electrical machine (1), wherein the final control element (8) can be activated via the control device (5), and wherein a pressure switch (16) for monitoring the pressure in the at least one compressed air tank (4) and for influencing at least the speed of the electrical machine (1) is disposed in the compressed-air-carrying line (6) downstream of the compressor (3). Furthermore, the invention also relates to a method for controlling the compressor system according to the invention, wherein the compressor (3) is operated at a variable speed, assuming any intermediate value between the maximum speed (m) and the minimum speed (i), and wherein the pressure switch (16) monitors the pressure in the at least one compressed air tank (4) and has an indirect influence at least on the speed of the electrical machine (1).

IPC 8 full level
F04B 35/04 (2006.01); **F04B 41/02** (2006.01); **F04B 49/06** (2006.01); **F04B 49/08** (2006.01); **F04B 49/20** (2006.01); **F04C 28/08** (2006.01);
F04D 25/06 (2006.01); **F04D 27/00** (2006.01)

CPC (source: EP KR RU US)
B61D 27/00 (2013.01 - US); **B61L 25/021** (2013.01 - US); **B61L 25/025** (2013.01 - US); **F04B 35/04** (2013.01 - EP KR US);
F04B 41/02 (2013.01 - EP KR US); **F04B 49/06** (2013.01 - EP KR US); **F04B 49/08** (2013.01 - EP KR US); **F04B 49/20** (2013.01 - EP KR US);
B61L 2205/04 (2013.01 - US); **F04B 35/04** (2013.01 - RU); **F04B 2203/0209** (2013.01 - EP KR US); **F04B 2205/05** (2013.01 - EP KR US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2015082432 A1 20150611; AU 2014359381 A1 20160623; AU 2014359381 B2 20170914; CA 2932783 A1 20150611;
CN 105940221 A 20160914; CN 105940221 B 20180206; DE 102013113557 A1 20150611; EP 3077673 A1 20161012;
JP 2016539277 A 20161215; JP 6275257 B2 20180207; KR 20160093649 A 20160808; RU 2646988 C2 20180313;
US 2017002804 A1 20170105

DOCDB simple family (application)
EP 2014076166 W 20141202; AU 2014359381 A 20141202; CA 2932783 A 20141202; CN 201480074101 A 20141202;
DE 102013113557 A 20131205; EP 14808924 A 20141202; JP 2016536585 A 20141202; KR 20167017034 A 20141202;
RU 2016126788 A 20141202; US 201415101735 A 20141202