

Title (en)

METHOD FOR HYDROPHOBIZING AND/OR OLEOPHOBIZING A MATERIAL, AND HYDROPHOBIZED AND/OR OLEOPHOBIZED COMPONENT

Title (de)

VERFAHREN ZUR HYDROPHOBIERUNG UND/ODER OLEOPHOBIERUNG EINES WERKSTOFFS SOWIE HYDROPHOBIERTES UND/ODER OLEOPHOBIERTES BAUTEIL

Title (fr)

PROCÉDÉS D'HYDROPHOBISATION OU D'OLÉOPHOBISATION D'UN MATÉRIAUX ET ÉLÉMENT HYDROPHOBISÉ OU OLÉOPHOBISÉ

Publication

EP 3083076 A1 20161026 (DE)

Application

EP 15707284 A 20150106

Priority

- DE 102013226215 A 20131217
- EP 2015050093 W 20150106

Abstract (en)

[origin: WO2015161933A1] The invention relates to methods for hydrophobizing and/or oleophobizing a material. The method involves the following steps: - charging a compressed gas (22) with a water repellent and/or oil repellent (21); - bringing the material (15) in contact with the compressed, charged gas (20); and - eliminating the gas (20) from the material (15). The invention further relates to a component of an electric machine, comprising or made of a material. According to the invention, a water repellent and/or an oil repellent can be detected down to a depth of at least 1mm in the material in an area located near the surface of the material.

IPC 8 full level

B05D 1/18 (2006.01); **B05D 5/08** (2006.01)

CPC (source: CN EP)

B05D 1/18 (2013.01 - CN EP); **B05D 5/08** (2013.01 - CN EP); **B05D 5/083** (2013.01 - CN EP); **B05D 7/02** (2013.01 - CN EP);
B05D 1/025 (2013.01 - CN EP); **B05D 2401/90** (2013.01 - CN EP)

Citation (search report)

See references of WO 2015161933A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102013226215 A1 20150618; CN 105992654 A 20161005; EP 3083076 A1 20161026; EP 3083076 B1 20200311;
WO 2015161933 A1 20151029

DOCDB simple family (application)

DE 102013226215 A 20131217; CN 201580002998 A 20150106; EP 15707284 A 20150106; EP 2015050093 W 20150106