

Title (en)

METHOD AND DEVICE FOR MAINTENANCE AND PROTECTION OF A HYDRAULIC CONNECTION

Title (de)

VERFAHREN UND VORRICHTUNG ZUR WARTUNG UND ZUM SCHUTZ EINER HYDRAULISCHEN VERBINDUNG

Title (fr)

PROCÉDÉ ET DISPOSITIF POUR LA MAINTENANCE ET LA PROTECTION D'UNE LIAISON HYDRAULIQUE

Publication

EP 3085541 B1 20180912 (EN)

Application

EP 16163331 A 20160331

Priority

- FR 1552875 A 20150402
- FR 1554355 A 20150513

Abstract (en)

[origin: EP3085541A1] The invention relates to a method of cleaning an ink circuit of an inkjet printer, comprising at least one reservoir (10), called the main reservoir, at least one ink cartridge (30), a first pump (31) to pump ink from the cartridge, first fluid connection means (346, 35, 33343, 344, 347) to transfer ink from the ink cartridge (30) to the reservoir (10), a second pump (20) to pump ink from said reservoir (10), second fluid connection means (37, 319, 320) to transfer ink to the ink cartridge, and control means (3), this method comprising at least: a) a step in which ink is transferred from the main reservoir (10) as far as the cartridge (30), through the second pump (20) and the second fluid connection means, b) a step to pump at least part of the ink transferred during step a) to the main reservoir (10).

IPC 8 full level

B41J 2/18 (2006.01); **B41J 2/175** (2006.01); **B41J 2/185** (2006.01); **B41J 2/20** (2006.01)

CPC (source: EP)

B41J 2/1707 (2013.01); **B41J 2/17546** (2013.01); **B41J 2/17566** (2013.01); **B41J 2/18** (2013.01); **B41J 2/185** (2013.01); **B41J 2002/17579** (2013.01)

Cited by

CN116100955A; CN109649013A; CN118560159A; EP4023445A1; EP4023444A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3085541 A1 20161026; EP 3085541 B1 20180912

DOCDB simple family (application)

EP 16163331 A 20160331