

Title (en)
INTER-DOMAIN SDN TRAFFIC ENGINEERING

Title (de)
SDN-VERKEHRSTECHNIK ZWISCHEN DOMÄNEN

Title (fr)
INGÉNIERIE DU TRAFIC SDN INTER-DOMAINES

Publication
EP 3090517 A4 20161123 (EN)

Application
EP 15744082 A 20150127

Priority

- US 201414168682 A 20140130
- US 2015013064 W 20150127
- US 201314141077 A 20131226

Abstract (en)
[origin: WO2015096758A1] Hierarchical Software Defined Network (SDN) architectures can be used to reduce complexity of traffic engineering in large or divers network environments. In hierarchical SDN architectures, a network is sub-divided into multiple regions, and each region is assigned to a different SDN controller. Network status information is collected and consolidated at a regional level, and fed upstream through the SDN control plane until it reaches a root SDN controller. The root-SDN controller computes cost-based parameters, which are distributed to regional SDN controllers for local provisioning. The cost-based parameters can include Lagrangian variables estimations or other parameters that constrain regional traffic engineering optimization in a manner that advances global traffic engineering objectives.

IPC 8 full level
H04L 47/52 (2022.01); **H04L 47/724** (2022.01); **H04L 47/80** (2022.01)

CPC (source: EP US)
H04L 41/044 (2013.01 - EP US); **H04L 41/0896** (2013.01 - EP US); **H04L 41/40** (2022.05 - EP); **H04L 43/04** (2013.01 - EP US); **H04L 43/06** (2013.01 - EP US); **H04L 43/20** (2022.05 - EP); **H04L 45/04** (2013.01 - US); **H04L 47/125** (2013.01 - US); **H04L 47/70** (2013.01 - US); **H04L 47/724** (2013.01 - US); **H04L 47/782** (2013.01 - EP US); **H04L 47/785** (2013.01 - EP US); **H04L 47/827** (2013.01 - US); **H04L 47/83** (2022.05 - EP); **H04L 67/02** (2013.01 - US); **H04L 43/0817** (2013.01 - EP US); **H04L 45/64** (2013.01 - US); **H04L 47/805** (2013.01 - US)

Citation (search report)

- [Y] US 2013329601 A1 20131212 - YIN HONGTAO [US], et al
- [A] US 2013250770 A1 20130926 - ZOU TING [US], et al
- [Y] CHAMANIA M ET AL: "An adaptive inter-domain PCE framework to improve resource utilization and reduce inter-domain signaling", OPTICAL SWITCHING AND NETWORKING, ELSEVIER, NL, vol. 6, no. 4, 31 December 2009 (2009-12-31), pages 259 - 267, XP026736384, ISSN: 1573-4277, [retrieved on 20090915], DOI: 10.1016/J.OSN.2009.08.007
- [A] WU D WANG HUAWEI S PREVIDI CISCO H GREDLER JUNIPER S RAY Q: "BGP attribute for North-Bound Distribution of Traffic Engineering (TE) performance Metrics; draft-wu-idr-te-pm-bgp-03.txt", BGP ATTRIBUTE FOR NORTH-BOUND DISTRIBUTION OF TRAFFIC ENGINEERING (TE) PERFORMANCE METRICS; DRAFT-WU-IDR-TE-PM-BGP-03.TXT, INTERNET ENGINEERING TASK FORCE, IETF; STANDARDWORKINGDRAFT, INTERNET SOCIETY (ISOC) 4, RUE DES FALAISES CH- 1205 GENEVA, SWITZ, 21 October 2013 (2013-10-21), pages 1 - 14, XP015095807
- See references of WO 2015116580A1

Cited by
EP3618370A4; US11290568B2

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2015096758 A1 20150702; CN 105960783 A 20160921; CN 105960783 B 20191018; CN 106105117 A 20161109; CN 106105117 B 20190920; EP 3053312 A1 20160810; EP 3053312 A4 20161102; EP 3090517 A1 20161109; EP 3090517 A4 20161123; EP 3090517 B1 20180124; US 10009287 B2 20180626; US 2015188837 A1 20150702; US 2015215235 A1 20150730; US 9559980 B2 20170131; WO 2015116580 A1 20150806

DOCDB simple family (application)
CN 2014094894 W 20141225; CN 201480068294 A 20141225; CN 201580006817 A 20150127; EP 14874903 A 20141225; EP 15744082 A 20150127; US 201314141077 A 20131226; US 201414168682 A 20140130; US 2015013064 W 20150127