

Title (en)  
LIFTING DEVICE

Title (de)  
HUBVORRICHTUNG

Title (fr)  
DISPOSITIF DE LEVAGE

Publication  
**EP 3138807 A1 20170308 (DE)**

Application  
**EP 15183810 A 20150904**

Priority  
EP 15183810 A 20150904

Abstract (en)  
[origin: WO2017037085A1] The invention relates to a lifting apparatus suitable for an industrial processing station, in particular a lifting table suitable for conveying a body shell in the series production of motor vehicles, wherein the lifting apparatus is designed to convey a workpiece on a top frame (8) moved in a purely vertical direction. In this case, the lifting apparatus has, as first vertical guide, at least one isosceles slider-crank mechanism (1, 2, 3, 4, 5) actuated by a motorized drive element (13+6, 7, 9, 12). In this case, the isosceles slider-crank mechanism, which consists of a fixed-bearing swing arm (6) with the swing-arm bearing (4) thereof, a control arm (3) with the control-arm guide (5) thereof, a control-arm central joint (2) and a fixed-bearing joint (1) connected to the top frame (8), is configured such that it is moved by the actuation of the tie rod (9) acting on the fixed-bearing swing arm (6). In particular the use of an isosceles slider-crank mechanism, which is also known in the literature as a "Scott-Russel mechanism", provides a simple and effective variant of a vertical guide system which allows low overall heights with minimum production outlay.

Abstract (de)  
Die Erfindung betrifft eine Hubvorrichtung für eine industrielle Bearbeitungsstation, insbesondere ein Hubtisch für die Förderung einer Rohkarosse in der Kraftfahrzeug-Serienfertigung, wobei die Hubvorrichtung zur Förderung eines Werkstücks auf einem rein vertikaler Richtung bewegten Oberrahmen [8] ausgestaltet ist. Dabei weist die Hubvorrichtung zumindest eine mit einem motorischen Antriebselement [13 + 6, 7, 9, 12] betätigten gleichschenkligen Geradschubkurbel [1, 2, 3, 4, 5] als erste Vertikalführung auf. Insbesondere durch den Einsatz einer gleichschenkligen Geradschubkurbel, die in der Literatur auch als "Scott-Russel-Mechanismus" bekannt ist, ist eine einfache und effektive Variante eines vertikalen Führungssystems gegeben, welche geringe Bauhöhen bei minimalem Fertigungsaufwand ermöglicht.

IPC 8 full level  
**B66F 7/06** (2006.01)

CPC (source: EP US)  
**B66F 7/065** (2013.01 - US); **B66F 7/0658** (2013.01 - US); **B66F 7/0691** (2013.01 - EP US)

Citation (applicant)  
• DE 102008036288 A1 20100218 - EXPERT TUENKERS GMBH [DE]  
• DE 20209407 U1 20030731 - REMECH SYSTEMTECHNIK GMBH & CO [DE]

Citation (search report)  
• [XAY] CN 103011013 A 20130403 - ANHUI JEE AUTOMATION EQUIPMENT  
• [XAY] EP 2719653 A1 20140416 - EXPERT TUENKERS GMBH [DE]  
• [YA] FR 2912393 A1 20080815 - PEUGEOT CITROEN AUTOMOBILES SA [FR]  
• [YA] JP S53165591 U 19781225  
• [A] US 4886145 A 19891212 - IWAHASHI KUNIMITSU [JP]  
• [A] JP S56122798 A 19810926 - NAGOYA KIKO KK  
• [A] GB 2179016 A 19870225 - LAMB TECHNICON CORP  
• [A] US 2132343 A 19381004 - JARRETT GEORGE E

Cited by  
CN107161598A; CN114545779A

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**EP 3138807 A1 20170308**; BR 112018003974 A2 20180925; BR 112018003974 B1 20220118; CN 107922176 A 20180417;  
CN 107922176 B 20190802; EP 3319901 A1 20180516; EP 3319901 B1 20190821; ES 2758103 T3 20200504; MX 2018002556 A 20180528;  
PL 3319901 T3 20200228; PT 3319901 T 20191014; US 10843911 B2 20201124; US 2018273362 A1 20180927; WO 2017037085 A1 20170309

DOCDB simple family (application)  
**EP 15183810 A 20150904**; BR 112018003974 A 20160831; CN 201680048887 A 20160831; EP 16762756 A 20160831;  
EP 2016070457 W 20160831; ES 16762756 T 20160831; MX 2018002556 A 20160831; PL 16762756 T 20160831; PT 16762756 T 20160831;  
US 201615757206 A 20160831