

Title (en)
METHOD FOR PRODUCING DECORATED WOODEN COMPOSITE BOARDS AND PANEL PRODUCED FROM THE WOODEN COMPOSITE BOARD, IN PARTICULAR FLOOR PANEL

Title (de)
VERFAHREN ZUM HERSTELLEN DEKORierter HOLZWERKSTOFFPLATTEN UND AUS DER HOLZWERKSTOFFPLATTE HERGESTELLTES PANEEL, INSBESONDERE FUSSBODENPANEEL

Title (fr)
PROCÉDÉ DE FABRICATION DE PANNEAUX DÉRIVÉS DU BOIS DÉCORÉS ET LAMBRIS, EN PARTICULIER LAMBRIS DE PLANCHER, FABRIQUÉ À PARTIR DE PANNEAUX DÉRIVÉS DU BOIS

Publication
EP 3140130 B1 20201007 (DE)

Application
EP 15721577 A 20150508

Priority

- EP 14001642 A 20140509
- EP 2015000942 W 20150508

Abstract (en)
[origin: CA2948202A1] A method for producing decorated wooden composite boards having the following steps: a) sprinkling of glued wood fibres or wood chips to form a wooden composite cake, b) pressing of the wooden composite cake under the influence of elevated temperature to form a support plate which is provided in a press-finished state and has a press skin which arises during the production thereof at least on one of the upper sides thereof, c) applying of a base coat made from a melamine-based liquid resin to the preferably untreated press skin of the upper side of the support plate, wherein the resin penetrates at least partially into the upper edge layer of the support plate and in the process at least partially penetrates and improves the press skin, d) drying of the base coat, e) applying of a base colour to the base coat layer, f) drying of the base colour, g) applying of at least one water-based printing ink enriched with pigments onto the dried base colour in order to produce a decorative pattern, h) drying of the decorative pattern, i) applying of a seal made from at least one melamine-based resin to the decorative layer, j) drying of the seal, k) pressing of the support plate with the base coat applied on the upper side, base colour, decorative pattern and seal and with a counteracting layer applied on the lower side with the application of pressure and temperature in order to form a laminate which is distinguished by the fact that a water-based ink is used as base colour, which water-based ink is applied to the dried base coat by means of a digital printer, and that the resin for sealing is applied in liquid form.

IPC 8 full level
B44C 5/04 (2006.01); **B27N 7/00** (2006.01)

CPC (source: CN EP RU US)
B27N 3/02 (2013.01 - US); **B27N 3/04** (2013.01 - US); **B27N 3/08** (2013.01 - RU US); **B27N 7/005** (2013.01 - CN EP RU US);
B44C 5/04 (2013.01 - CN EP US); **B44C 5/0476** (2013.01 - CN EP RU US); **E04F 15/102** (2013.01 - CN EP RU US);
B41M 1/38 (2013.01 - CN EP US); **B41M 5/0076** (2013.01 - CN EP US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2942207 A1 20151111; **EP 2942207 B1 20180704**; CA 2948202 A1 20151112; CA 2948202 C 20210615; CN 106457602 A 20170222; CN 106457602 B 20191203; DK 2942207 T3 20181008; EP 3140130 A1 20170315; EP 3140130 B1 20201007; EP 3378675 A1 20180926; ES 2683714 T3 20180927; ES 2833160 T3 20210614; HR P20181299 T1 20181005; HR P20202079 T1 20210219; PL 2942207 T3 20181130; PL 3140130 T3 20210614; PT 2942207 T 20181008; PT 3140130 T 20201207; RU 2016140386 A 20180609; RU 2016140386 A3 20181203; RU 2678393 C2 20190128; UA 119346 C2 20190610; US 10059030 B2 20180828; US 2017120474 A1 20170504; WO 2015169450 A1 20151112

DOCDB simple family (application)
EP 14001642 A 20140509; CA 2948202 A 20150508; CN 201580023747 A 20150508; DK 14001642 T 20140509; EP 15721577 A 20150508; EP 18172119 A 20140509; EP 2015000942 W 20150508; ES 14001642 T 20140509; ES 15721577 T 20150508; HR P20181299 T 20180809; HR P20202079 T 20201231; PL 14001642 T 20140509; PL 15721577 T 20150508; PT 14001642 T 20140509; PT 15721577 T 20150508; RU 2016140386 A 20150508; UA A201610487 A 20150508; US 201515302809 A 20150508