

Title (en)
TOOL HOLDER BASE INSERT, TOOL HOLDER ARRANGEMENT AND METHOD FOR INSTALLING THE AT LEAST ONE TOOL HOLDER BASE INSERT IN THE TOOL HOLDER ARRANGEMENT

Title (de)
WERKZEUGHALTERBASISEINSATZ, WERKZEUGHALTERANORDNUNG UND VERFAHREN ZUM MONTIEREN DES MINDESTENS EINEN WERKZEUGHALTERBASISEINSATZES IN DER WERKZEUGHALTERANORDNUNG

Title (fr)
INSERT DE BASE DE SUPPORT D'OUTILS, SYSTÈME DE SUPPORT D'OUTILS ET PROCÉDÉ DE MONTAGE D'AU MOINS UN INSERT DE BASE DE SUPPORT D'OUTILS DANS LE SYSTÈME DE SUPPORT D'OUTILS

Publication
EP 3142519 A1 20170322 (DE)

Application
EP 15725527 A 20150512

Priority
• DE 102014106731 A 20140513
• EP 2015060433 W 20150512

Abstract (en)
[origin: WO2015173218A1] The invention is based on the object of proposing a tool holder base insert for a perforated panel, which forms an alternative to the known holders. This object is achieved by a tool holder base insert 3 for a perforated panel 2; 2a, b, c having a bearing surface 11 for bearing the tool holder base insert 3 on the perforated panel 2; 2c in an installed state of the tool holder base insert 3, having at least one hook device 8, wherein the hook device 8 projects beyond the bearing surface 11 in a plug-in direction E, and therefore the hook device 8, in the installed state of the tool holder base insert 3, can engage through one of the accommodating holes 4, wherein, in the installed state of the tool holder base insert 3, a peripheral panel region is arranged in a panel-accommodating region 9, and having at least one securing device 14, wherein the securing device 14, in the installed state of the tool holder base insert 3, is arranged in one of the accommodating holes 4 and secures the tool holder base insert 3 in a form-fitting manner against being displaced counter to the loading direction B, wherein the tool holder base insert 3 has a main-body portion 5 and a securing portion 6, wherein the main-body portion 5 defines the bearing surface 11 and carries the hook device 8, and wherein the securing portion 6 carries the securing device 14, wherein the main-body portion 5 and the securing portion 6 are arranged for movement in relation to one another, and therefore the securing device 14 can be deflected elastically, counter to the plug-in direction E, relative to the hook device 8.

IPC 8 full level
A47F 5/08 (2006.01); **B25H 3/04** (2006.01)

CPC (source: EP)
B25H 3/04 (2013.01); **E06B 1/02** (2013.01); **A47F 5/0823** (2013.01)

Citation (search report)
See references of WO 2015173218A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
DE 102014106731 A1 20151119; DE 202014011040 U1 20170705; EP 3142519 A1 20170322; EP 3142519 B1 20191016; PL 3142519 T3 20200430; WO 2015173218 A1 20151119

DOCDB simple family (application)
DE 102014106731 A 20140513; DE 202014011040 U 20140513; EP 15725527 A 20150512; EP 2015060433 W 20150512; PL 15725527 T 20150512