

Title (en)

HEEL-PROTECTING DEVICE, HEEL-PROTECTING SYSTEM, AND HEEL-PROTECTING DEVICE ASSORTMENT

Title (de)

ABSATZSCHUTZVORRICHTUNG SOWIE ABSATZSCHUTZSYSTEM

Title (fr)

DISPOSITIF DE PROTECTION DE TALON, SYSTÈME DE PROTECTION DE TALON AINSI QUE GAMME DE DISPOSITIFS DE PROTECTION DE TALON

Publication

EP 3160281 A1 20170503 (DE)

Application

EP 15739184 A 20150624

Priority

- DE 102014108910 A 20140625
- EP 2015064227 W 20150624

Abstract (en)

[origin: WO2015197676A1] The invention relates to a heel-protecting device (2) for shoes (1) having a heel (6) and having a sole (8) spaced apart from the heel (6) in the direction of a shoe longitudinal extent, preferably for high-heeled shoes having a stiletto heel, comprising supporting means (4) for enlarging the stepping surface (17) of the heel (6) of the shoe (1), which supporting means comprise a heel-supporting segment (5) for the heel (6), a sole-supporting segment (7) for the sole (8), and a connecting segment (10), which connects the heel-supporting segment (5) and the sole-supporting segment (7) to each other, preferably integrally, along the shoe longitudinal extent in order to bridge the distance between the heel (6) and the sole (8), wherein the heel-protecting device (1) has fastening means (3) associated with the supporting means (4) for detachably fastening the supporting means (4) to the shoe (1), wherein the supporting means (4) are more rigid than the fastening means (3) and wherein the fastening means (3) comprise a front pocket (12) for surrounding a front shoe tip (11) of the shoe (1) and a rear pocket (14) for surrounding an upper (13) of the shoe (1), which upper bears the heel (6). According to the invention, the fastening means (3) can be elastically extended in the direction of the shoe longitudinal extent in a region forming a stepping surface (17) for contacting an underlying surface, the stepping surface (17) being simultaneously enlarged, in such a way that heel-protecting device (2) can be fastened to the shoe (1), in particular exclusively, by extending the fixing means (3) and placing the fixing means in tension between the front shoe tip (11) and the upper (13).

IPC 8 full level

A43B 3/16 (2006.01)

CPC (source: EP)

A43B 3/16 (2013.01)

Citation (search report)

See references of WO 2015197676A1

Cited by

IT201800009781A1; WO2020084588A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102014108910 A1 20151231; EP 3160281 A1 20170503; EP 3160281 B1 20190227; WO 2015197676 A1 20151230

DOCDB simple family (application)

DE 102014108910 A 20140625; EP 15739184 A 20150624; EP 2015064227 W 20150624