

Title (en)
HIGH-STRENGTH ONE-TOUCH REBAR COUPLER

Title (de)
HOCHFESTER BEWEHRUNGSSTABKUPPLER MIT EINER BERÜHRUNG

Title (fr)
DISPOSITIF D'ACCOUPLEMENT DE BARRE D'ARMATURE À CONTACT UNIQUE À HAUTE RÉSISTANCE

Publication
EP 3168385 A4 20180314 (EN)

Application
EP 15819286 A 20150707

Priority
• KR 20140084811 A 20140707
• KR 20150011501 A 20150123
• KR 2015006985 W 20150707

Abstract (en)
[origin: EP3168385A1] A high-strength one-touch rebar coupler according to the present invention comprises: a coupler body having a hollow portion formed in the longitudinal direction, the coupler body being formed in a helical shape so as to provide the inner peripheral surface of the hollow portion with a rebar fastening force in the circumferential direction, and the coupler body comprising a first guide helix coupling portion, which has first guide sloping portions that slope from the center portion of the hollow portion towards the outside of one side thereof, and a second guide helix coupling portion, which has second guide sloping portions that slope from the center portion of the hollow portion towards the outside of the other side thereof; a first fastening unit screw-coupled to the first guide helix coupling portion of the coupler body and inserted into one side of the hollow portion, the first fastening unit comprising a plurality of first fastening members, which are coupled to the first guide sloping portions so as to be able to slide, respectively, each of the first fastening members having a first fastening helix coupling portion, which has a first fastening sloping portion, provided on the outer peripheral surface thereof and having a first grasping portion, which grasps the outer peripheral surface of a rebar for connection, provided on the inner peripheral surface thereof such that, when tensile forces act on coupled rebars, the first fastening members move in the opposite direction of the radial direction and thereby provide the rebars with fastening forces; and a second fastening unit screw-coupled to the second guide helix coupling portion of the coupler body and inserted into one side of the hollow portion, the second fastening unit comprising a plurality of second fastening members, which are coupled to the second guide sloping portions so as to be able to slide, respectively, each of the second fastening members having a second fastening helix coupling portion, which has a second fastening sloping portion, provided on the outer peripheral surface thereof and having a second grasping portion, which grasps the outer peripheral surface of a rebar for connection, provided on the inner peripheral surface thereof such that, when tensile forces act on coupled rebars, the second fastening members move in the radial direction and thereby provide the rebars with fastening forces.

IPC 8 full level
E04C 5/16 (2006.01); **E04C 5/18** (2006.01)

CPC (source: EP RU US)
E04C 5/16 (2013.01 - RU US); **E04C 5/165** (2013.01 - EP RU US); **E04C 5/18** (2013.01 - RU US)

Citation (search report)
• [X] KR 100725527 B1 20070608 - SAMYANG SYSTEM AND CONTROL CO [KR]
• [X] KR 20010001355 U 20010115
• [A] WO 9905375 A1 19990204 - CHUNG GYENG OK [KR]
• [A] KR 20100090330 A 20100816 - KIM BYUNG SUB [KR]
• [A] KR 101030579 B1 20110421 - HONG MAN KI [KR], et al
• See references of WO 2016006904A1

Cited by
CN110388361A

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 3168385 A1 20170517; **EP 3168385 A4 20180314**; BR 112017000253 A2 20171114; CN 106661887 A 20170510; JP 2017528627 A 20170928; PH 12017500043 A1 20170522; RU 2017100552 A 20180712; RU 2017100552 A3 20180712; RU 2667990 C2 20180925; US 10385569 B2 20190820; US 2017204608 A1 20170720; WO 2016006904 A1 20160114

DOCDB simple family (application)
EP 15819286 A 20150707; BR 112017000253 A 20150707; CN 201580036830 A 20150707; JP 2017522304 A 20150707; KR 2015006985 W 20150707; PH 12017500043 A 20170106; RU 2017100552 A 20150707; US 201515324705 A 20150707