

Title (en)

BRAKING SYSTEM FOR GYMNASTIC MACHINES AND OPERATING METHOD THEREOF

Title (de)

BREMSSYSTEM FÜR GYMNASTISCHE MASCHINEN UND BETRIEBSVERFAHREN DAVON

Title (fr)

SYSTÈME DE FREINAGE POUR MACHINES GYMNASTIQUES ET PROCÉDÉ DE FONCTIONNEMENT

Publication

EP 3181197 A1 20170621 (EN)

Application

EP 16198647 A 20161114

Priority

IT UB20159645 A 20151217

Abstract (en)

The present invention concerns a braking system (S), installable on gymnastic passive machines, of the type having one rotating member such as a flywheel and the like, on which magnetic braking members are arranged, capable to generate a magnetic braking force on said flywheel, comprising: a magnetic sensor (1), arranged in proximity of said magnetic braking members, so as to detect the intensity of the magnetic field induced from said braking members on said flywheel, an angular velocity sensor (4), for measuring the rotation velocity of said flywheel, characterized in that said braking system (S) comprises a second magnetic sensor (2), arranged at a predetermined distance, preferably comprised between 5 and 15 cm, from said first magnetic sensor (1), to measure the magnetic field induced on said flywheel as conditioned by the structure of said gymnastic machines; in that said braking system (S) comprises a temperature sensor (3) arranged in correspondence of said first magnetic sensor (1), to detect the temperature of said flywheel; and in that said braking system (S) comprises one control logic unit (5), operatively connected to said first (1) and second (2) magnetic sensor, to said temperature sensor (3) and to said angular velocity sensor (4), in which nominal calibration values are stored, said control logic unit (5) being capable to acquire and process the electric signals from said first magnetic sensor (1), from said second magnetic sensor (2) and from said temperature sensor (3), so as to calculate the actual braking magnetic force generated by said magnetic members on said flywheel, during the operation of said gymnastic machine, correcting said calculation after a comparison between the data acquired from said sensors and said stored nominal calibration values. The present invention also concerns an operating method of said system.

IPC 8 full level

A63B 21/005 (2006.01)

CPC (source: EP)

A63B 21/005 (2013.01); **A63B 2220/34** (2013.01); **A63B 2220/58** (2013.01); **A63B 2220/72** (2013.01); **A63B 2220/833** (2013.01)

Citation (search report)

- [Y] US 2008207402 A1 20080828 - FISHER JOHN [US], et al
- [Y] US 6513395 B1 20030204 - JONES CHRISTOPHER A [US]
- [A] US 2011152039 A1 20110623 - HENDRICKSON RICK W [US], et al
- [A] US 2011195818 A1 20110811 - SCHROEDER BRADY [US], et al
- [A] WO 2006107266 A2 20061012 - YOYO TECHNOLOGY AB [SE], et al

Cited by

CN113975711A; WO2023040773A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 3181197 A1 20170621; **EP 3181197 B1 20180829**; IT UB20159645 A1 20170617

DOCDB simple family (application)

EP 16198647 A 20161114; IT UB20159645 A 20151217