

Title (en)

ASSEMBLIES COMPRISING A RAILWAY RAIL SIDE POST INSULATOR AND RAILWAY RAIL CLIP ANCHORING DEVICE FOR USE THEREWITH

Title (de)

ANORDNUNGEN MIT EINEM EISENBAHNSCHIENENSEITENPFOSTENISOLATOR UND EISENBAHNSCHIENENKLAMMERVERANKERUNGSVORRICHTUNG ZUR VERWENDUNG DAMIT

Title (fr)

ENSEMBLES COMPRENANT UN ISOLATEUR DE MONTANT LATÉRAL DE RAIL DE CHEMIN DE FER ET DISPOSITIF D'ANCRAGE D'ATTACHE DE RAIL DE CHEMIN DE FER DESTINÉ À ÊTRE UTILISÉ AVEC CEUX-CI

Publication

EP 3183389 A1 20170628 (EN)

Application

EP 15744310 A 20150724

Priority

- GB 201414595 A 20140818
- GB 2015052146 W 20150724

Abstract (en)

[origin: WO2016027059A1] In an assembly comprising a first railway rail side post insulator and a railway rail clip anchoring device (3), for retaining a resilient railway rail fastening clip (6), which device (3) is configured to support the first railway rail side post insulator (1'), the first railway rail side post insulator (1') is configured to provide an electrically-insulating load bearing face (10') between an upright side face (21 A) of a foot (21) of a railway rail (2) and upright load bearing faces (301, 302, 303, 304) of a railway rail clip anchoring device (3) located adjacent to the rail foot (21), the electrically-insulating load bearing face (10') being provided by an outer face of a wall (100') of the insulator. The insulator further comprises a member (110'), joined to an inner face (12') of the wall (100'), which member (110') has a top surface (11') which extends in a substantially perpendicular direction with respect to the load bearing face (10') to a depth (do) from the inner face of the wall (100') which is greater than or substantially equal to a depth (dw) of the wall in the said direction. The railway rail clip anchoring device (3) has upright load bearing faces (301, 302, 303, 304), comprising front wall faces (301, 303, 304) configured for location adjacent to the rail foot (21), and an upper central face (302) which is offset from the front wall faces (301, 303, 304) by an offset distance (D) which is between a tenth and a half of the depth (D0) of the anchoring device (3) in a direction substantially perpendicular to the front wall faces (301, 303, 304), and an upwardly-facing surface (31) of the anchoring device (3) which extends from the upper central face (302) to provide a shelf portion (31) for receiving part (43) of the first railway rail side post insulator (1').

IPC 8 full level

E01B 9/66 (2006.01); **E01B 9/30** (2006.01)

CPC (source: CN EP RU)

E01B 9/00 (2013.01 - CN); **E01B 9/28** (2013.01 - CN); **E01B 9/30** (2013.01 - RU); **E01B 9/303** (2013.01 - EP); **E01B 9/62** (2013.01 - CN); **E01B 9/66** (2013.01 - EP RU)

Cited by

RU205994U1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2016027059 A1 20160225; AU 2015305007 A1 20170202; AU 2015305007 B2 20190829; BR 112017003132 A2 20171128; CN 106574448 A 20170419; CN 106574448 B 20180629; DK 3183389 T3 20190603; EP 3183389 A1 20170628; EP 3183389 B1 20190320; GB 201414595 D0 20141001; RU 2017108803 A 20180925; RU 2017108803 A3 20190118; RU 2691466 C2 20190614

DOCDB simple family (application)

GB 2015052146 W 20150724; AU 2015305007 A 20150724; BR 112017003132 A 20150724; CN 201580044069 A 20150724; DK 15744310 T 20150724; EP 15744310 A 20150724; GB 201414595 A 20140818; RU 2017108803 A 20150724