

Title (en)

SAFETY GRIP FOR A TRIGGER CORD OF A BLIND

Title (de)

SICHERHEITSGRIFF FÜR EINE AUSLÖSERSCHNUR EINER JALOUSIE

Title (fr)

POIGNÉE DE SÉCURITÉ POUR CORDE DE DÉCLENCHEMENT D'UN STORE

Publication

**EP 3201416 B1 20200101 (EN)**

Application

**EP 15826197 A 20151001**

Priority

- NL 2013571 A 20141003
- NL 2015050686 W 20151001

Abstract (en)

[origin: WO2016053101A1] A safety handgrip (1) comprises a frame (5) in which a redirection element (13) for the pull cord is movable. This redirection element (13) redirects the pull cord (11) so that the pull cord forms a loop. Between a support element (15) fixed to the frame and a bounding wall of a recess (17) present in the redirection element (13) is located a spring (19) which presses the redirection element into a position of rest. A cutting blade (21) is fixed to the frame, which cutting blade is located within the loop of the pull cord (11). The cutting blade has a cutting edge (21A) which is directed towards the loop-forming section (11C) of the pull cord. The redirection element (13) can be moved to a cutting position against the spring force if pressure is exerted on the front side of the safety handgrip while the pull cord (11) is being held. In this cutting position the cutting blade (21) is moved to the loop-forming section (11C) of the pull cord and has cut through the pull cord.

IPC 8 full level

**E06B 9/326** (2006.01)

CPC (source: EP)

**E06B 9/326** (2013.01); **E06B 2009/3265** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**WO 2016053101 A1 20160407**; EP 3201416 A1 20170809; EP 3201416 B1 20200101; NL 2013571 B1 20161003

DOCDB simple family (application)

**NL 2015050686 W 20151001**; EP 15826197 A 20151001; NL 2013571 A 20141003