

Title (en)
PLUG

Title (de)
STECKVERBINDER

Title (fr)
CONNECTEUR ENFICHABLE

Publication
EP 3204991 A1 20170816 (DE)

Application
EP 15823493 A 20151005

Priority
• DE 102014114632 A 20141009
• DE 2015100412 W 20151005

Abstract (en)
[origin: WO2016055055A1] The invention relates to a plug for use as a disconnecter for current transformers. According to the invention, two types of short-circuiting means (5, 6) are provided in the plug. A first short-circuiting means (5) is used for diverting overvoltages by short-circuiting the electrical contacts in the plug. A second short-circuiting means (6) is provided for short-circuiting electrical contacts (3, 4) in the plug when the plug is not contacted. The short-circuiting means (5, 6) are designed in such a way that the first short-circuiting means (5) is used as a fuse when the second short-circuiting means (6) fails.

IPC 8 full level
H01R 13/66 (2006.01); **H01R 13/703** (2006.01); **H01R 13/713** (2006.01)

CPC (source: CN EP KR RU US)
H01F 38/32 (2013.01 - US); **H01R 13/66** (2013.01 - RU); **H01R 13/6666** (2013.01 - CN EP KR US); **H01R 13/703** (2013.01 - CN EP KR US); **H01R 13/7132** (2013.01 - CN EP KR US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2016055055 A1 20160414; CA 2960896 A1 20160414; CN 106797094 A 20170531; CN 106797094 B 20190510; EP 3204991 A1 20170816; JP 2017530536 A 20171012; KR 101939927 B1 20190117; KR 20170061163 A 20170602; RU 2668564 C1 20181002; US 2017279228 A1 20170928; US 9935406 B2 20180403

DOCDB simple family (application)
DE 2015100412 W 20151005; CA 2960896 A 20151005; CN 201580054374 A 20151005; EP 15823493 A 20151005; JP 2017518968 A 20151005; KR 20177011802 A 20151005; RU 2017109983 A 20151005; US 201515505848 A 20151005