

Title (en)

AN ARRANGEMENT FOR SUPPORTING A STEEL PILE IN AN IMPACT PILE DRIVING DEVICE, AN IMPACT PILE DRIVING DEVICE, AN IMPACT PILE DRIVING MACHINE, AND A METHOD FOR ARRANGING THE SUPPORT OF A STEEL PILE IN AN IMPACT PILE DRIVING DEVICE

Title (de)

VORRICHTUNG ZUR UNTERSTÜTZUNG EINES STAHLPFAHLS IN EINER PFAHLRAMMVORRICHTUNG, PFAHLRAMMVORRICHTUNG, PFAHLRAMMMASCHINE UND VERFAHREN ZUM ANORDNEN DER UNTERSTÜTZUNG EINES STAHLPFAHLS IN EINER PFAHLRAMMVORRICHTUNG

Title (fr)

AGENCEMENT DESTINÉ À SUPPORTER UN PIEU EN ACIER DANS UN DISPOSITIF DE BATTAGE DE PIEUX À PERCUSSION, DISPOSITIF DE BATTAGE DE PIEUX À PERCUSSION, MACHINE DE BATTAGE DE PIEUX À PERCUSSION, ET PROCÉDÉ DE MISE EN PLACE DU SUPPORT D'UN PIEU EN ACIER DANS UN DISPOSITIF DE BATTAGE DE PIEUX À PERCUSSION

Publication

**EP 3207185 B1 20191127 (EN)**

Application

**EP 15804863 A 20151016**

Priority

- FI 20145911 A 20141017
- FI 2015050703 W 20151016

Abstract (en)

[origin: WO2016059299A1] The invention relates to an arrangement for supporting a thin-walled steel pile (5; 17; 26; 35) in an impact pile driving device, the arrangement comprising a supporting surface (4; 14; 23; 31 ), to which the steel pile (5; 17; 26; 35) can be supported, and in which arrangement the supporting surface (4; 14; 23; 31 ) is provided with one or more absorbing surfaces (6; 16; 25; 33) to be placed against the end of the wall (8; 18; 26; 36) of the steel pile (5; 17; 26; 35). In the arrangement according to the invention, the absorbing surface (6; 16; 25; 33) is configured to shape the end of the wall (8; 18; 27; 36) of the steel pile (5; 17; 26; 35) coming against the absorbing surface (6; 16; 25; 33), by the effect of the impact driving of the steel pile (5; 17; 26; 35), so that at least the part of the wall (8; 18; 27; 36) at the absorbing surface (6; 16; 25; 33) of the wall (8; 18; 27; 36) is shaped against the absorbing surface (6; 16; 25; 33), wherein the movement of the wall (8; 18; 27; 36) in the direction of a plane transverse to the direction of impact driving of the steel pile is prevented, at least at the head of the steel pile (5; 17; 26; 35). Also, the absorbing surface (6; 16; 25; 33) in the supporting surface (4; 14; 23; 31 ) can be configured to be shaped by the effect of the impact driving of the steel pile (5; 17; 26; 35) so that the absorbing surface (6; 16; 25; 33) is shaped against the part of the wall (8; 18; 27; 36) of the steel pile (5; 17; 26; 35) at the absorbing surface (6; 16; 25; 33), whereby the movement of the wall (8; 18; 27; 36) at the head of the steel pile (5; 17; 26; 35) is prevented. The invention also relates to a method for arranging the support of a steel pile (5; 17; 26; 35) in an impact pile driving device.

IPC 8 full level

**E02D 5/28** (2006.01); **E02D 7/00** (2006.01); **E02D 7/08** (2006.01); **E02D 7/16** (2006.01); **E02D 13/10** (2006.01)

CPC (source: EP US)

**E02D 5/28** (2013.01 - EP US); **E02D 7/00** (2013.01 - EP US); **E02D 7/08** (2013.01 - EP US); **E02D 7/16** (2013.01 - EP US); **E02D 13/10** (2013.01 - EP US); **E02D 2200/1607** (2013.01 - EP US); **E02D 2200/1628** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**WO 2016059299 A1 20160421**; AU 2015332299 A1 20170427; AU 2015332299 B2 20200319; CA 2964044 A1 20160421; CA 2964044 C 20200714; CN 107532397 A 20180102; CN 107532397 B 20201124; DK 3207185 T3 20200224; EP 3207185 A1 20170823; EP 3207185 B1 20191127; ES 2769878 T3 20200629; HK 1245366 A1 20180824; PL 3207185 T3 20200601; PT 3207185 T 20200304; US 10557243 B2 20200211; US 2017268194 A1 20170921

DOCDB simple family (application)

**FI 2015050703 W 20151016**; AU 2015332299 A 20151016; CA 2964044 A 20151016; CN 201580069589 A 20151016; DK 15804863 T 20151016; EP 15804863 A 20151016; ES 15804863 T 20151016; HK 18102561 A 20180222; PL 15804863 T 20151016; PT 15804863 T 20151016; US 201515519575 A 20151016