Title (en)

**DIE-CAST SNAP BUTTON** 

Title (de

DRUCKGEGOSSENER SCHNAPPKNOPF

Title (fr)

**BOUTON-PRESSION COULÉ SOUS PRESSION** 

Publication

EP 3216363 B1 20181024 (EN)

Application

EP 17160295 A 20170310

Priority

IT UB20161200 A 20160311

Abstract (en)

[origin: EP3216363A1] A die-cast snap button or die-cast press stud, particularly for items of clothing or leather goods, including handbags, other leather accessories or the like, including a female section designed to anchor a male section in a fastening. The female section comprises a circular flat body (1) with a central hole (2) which is connected, at two sections opposite each other, at the lower part of a conical ring (3), coaxial to said hole, so creating an empty bilateral space. In said empty space an elastic rectangular body (6) is placed by the long side. To allow said placement, the elastic rectangular body presents a slot in the short side. The upper diameter (8) of the conical ring is smaller than the diameter of the hole in the circular flat body and the lower diameter (9) of the conical ring is larger than the short side of elastic body, just ensuring strong fastening and an excellent snap-action. The elastic body surrounds the conical ring and it's blocked into the lateral slots.

IPC 8 full level

A44B 17/00 (2006.01)

CPC (source: EP)

A44B 17/0011 (2013.01); A44B 17/0076 (2013.01)

Cited by

USD946894S; USD963344S; USD904829S; USD960648S; US11517086B2; US11685573B2; USD951643S; US11203465B2; USD985937S; USD1014965S; USD961926S; USD994438S; USD1014969S; US11976498B2; USD907445S; USD925299S; USD925991S; USD929814S; USD959208S; USD960656S; USD962010S; USD1033158S

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3216363 A1 20170913; EP 3216363 B1 20181024; IT UB20161200 A1 20170911

DOCDB simple family (application)

EP 17160295 A 20170310; IT UB20161200 A 20160311