

Title (en)

SEALING DEVICE FOR A SLIDABLE SASH AS A SLIDING SHASH OR SLIDABLE LIFT-AND-SLIDE SASH OF A WINDOW OR A DOOR

Title (de)

DICHTUNGSVORRICHTUNG FÜR EINEN VERSCHIEBBAREN FLÜGEL ALS SCHIEBEFLÜGEL ODER VERSCHIEBBAREN HEBE-SCHIEBEFLÜGEL EINES FENSTERS ODER EINER TÜR

Title (fr)

DISPOSITIF D'ÉTANCHÉITÉ POUR CHÂSSIS MOBILE UTILISÉ COMME CHÂSSIS COULISSANT OU CHÂSSIS LEVANT-COULISSANT MOBILE D'UNE FENÊTRE OU D'UNE PORTE

Publication

EP 3221540 B1 20190828 (DE)

Application

EP 15794878 A 20151110

Priority

- DE 202014009250 U 20141121
- EP 2015076137 W 20151110

Abstract (en)

[origin: WO2016078961A1] The invention relates to a sealing device (10) for a slidable leaf as a sliding leaf (3) or slidable lift-and-slide leaf of a window or a door, comprising sealing strips (11, 12), which are arranged in an impact region (9) of intermediate spaces (9') between the sliding leaf (3) and the fixed panel (4) for sealing and securing a closed sliding leaf (3) of a window or a door (1), of which in the impact region (9), a sealing strip (11) having a leaf frame contact surface (5") can be fastened to the leaf frame (5) of the sliding leaf (3), and a sealing strip (12) having a fixed panel frame contact surface (7") can be fastened to the fixed panel frame (7) of the further fixed panel (4). The sealing strips (11, 12) comprised of a profile body (13) have first profile sections (14), which mutually engage across or behind when the sliding leaf (3) is closed, and which form an operatively connected unit with the seals (15) arranged opposite thereof. On the side (16) parallelly facing away from the leaf frame contact surface (5") or the fixed panel contact surface (7"), the profile bodies (13) are provided with a receiving groove (17), into which mounting screws (18) can be inserted, and which, in the mounted state of the side (16), are arranged in a countersunk fashion. The receiving groove (17) accommodates a cover strip (19) in a form-fitting and/or force-locking manner, which cover strip (19) sealingly covers the receiving groove (17) such that the cover strip (19) is almost flush with the side (16).

IPC 8 full level

E06B 7/23 (2006.01); **E06B 3/263** (2006.01); **E06B 3/46** (2006.01); **E06B 3/52** (2006.01)

CPC (source: CN EP KR RU)

E06B 3/26305 (2013.01 - KR); **E06B 3/26347** (2013.01 - KR); **E06B 3/46** (2013.01 - EP RU); **E06B 3/4609** (2013.01 - KR);
E06B 3/52 (2013.01 - EP RU); **E06B 7/2305** (2013.01 - CN EP RU); **E06B 7/2307** (2013.01 - CN EP RU); **E06B 7/2309** (2013.01 - CN EP KR RU);
E05Y 2800/12 (2013.01 - KR); **E06B 3/26347** (2013.01 - CN); **E06B 3/4609** (2013.01 - CN); **E06B 3/469** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 202014009250 U1 20141215; CN 106795737 A 20170531; CN 106795737 B 20180928; EP 3221540 A1 20170927;
EP 3221540 B1 20190828; KR 20170086088 A 20170725; LT 3221540 T 20191010; PL 3221540 T3 20200228; RU 2017107728 A 20180910;
RU 2017107728 A3 20190327; RU 2708704 C2 20191211; WO 2016078961 A1 20160526

DOCDB simple family (application)

DE 202014009250 U 20141121; CN 201580052255 A 20151110; EP 15794878 A 20151110; EP 2015076137 W 20151110;
KR 20177016909 A 20151110; LT 15794878 T 20151110; PL 15794878 T 20151110; RU 2017107728 A 20151110