

Title (en)

METHOD AND DEVICE FOR FLEXIBLE, SELECTIVE SSDF RELAYING

Title (de)

VERFAHREN UND VORRICHTUNG FÜR FLEXIBLE, SELEKTIVE SSDF-WEITERLEITUNG

Title (fr)

PROCÉDÉ ET DISPOSITIF DE RELAYAGE SOUPLE ET SÉLECTIF SSDF

Publication

EP 3224978 B1 20190102 (FR)

Application

EP 15808769 A 20151130

Priority

- FR 1461661 A 20141128
- FR 2015053262 W 20151130

Abstract (en)

[origin: WO2016083764A1] The invention relates to a method for relaying messages via a relay and to the relay for relaying the messages. The relay (r) includes: - a reliability testing means that relates only to those messages assessed as having an error and taken in the form that said messages had before error detection, so as to be able to separate the reliable messages from the unreliable ones; and - a shaping means (ETU) including a channel interleaver and a modulator, said shaping means relating only to those messages assessed as being without error and to those messages assessed as having an error but reliable. Said shaping is carried out flexibly if at least one message assessed as having an error passes the reliability test.

IPC 8 full level

H04L 1/00 (2006.01); **H04B 7/155** (2006.01)

CPC (source: CN EP US)

H04L 1/004 (2013.01 - CN EP US); **H04L 1/0048** (2013.01 - CN EP US); **H04L 1/0076** (2013.01 - CN EP US);
H04B 7/15528 (2013.01 - CN EP US); **H04L 1/0068** (2013.01 - CN EP US); **H04M 13/00** (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2016083764 A1 20160602; CN 107005347 A 20170801; CN 107005347 B 20200901; EP 3224978 A1 20171004; EP 3224978 B1 20190102;
FR 3029375 A1 20160603; US 10313052 B2 20190604; US 2017331584 A1 20171116

DOCDB simple family (application)

FR 2015053262 W 20151130; CN 201580064477 A 20151130; EP 15808769 A 20151130; FR 1461661 A 20141128;
US 201515527559 A 20151130