

Title (en)

DELIVERY DEVICE HAVING TWO DISCHARGING STATIONS AND METHOD FOR ADJUSTING

Title (de)

AUSLAGEEINRICHTUNG MIT ZWEI ABGABESTATIONEN UND VERFAHREN ZUM EINSTELLEN

Title (fr)

DISPOSITIF DE SORTIE COMPRENANT DEUX POSTES DE DISTRIBUTION ET PROCÉDÉ D'AJUSTEMENT

Publication

**EP 3271174 B1 20200311 (DE)**

Application

**EP 16733072 A 20160628**

Priority

- DE 102015212063 A 20150629
- DE 102015218131 A 20150922
- DE 102016209116 A 20160525
- EP 2016064996 W 20160628

Abstract (en)

[origin: WO2017001394A2] The invention relates to a delivery device (03) for delivering printed sheets (B) which can be fed in the region of an inlet side of the delivery device (03), comprising at least one first discharge station (I; II) and one second discharge station (II; I) which is mounted downstream of the first discharge station (I; II) upstream in the transport path, the delivery stations (I; II) being associated respectively with a format or transport-relevant device (48; 49; 51; 52; 03; 139) which can be controlled by a drive comprising a control element (63; 106; 124; 147; 202) in view of adapting or correcting the guiding and/or delivery of the sheets in the relevant discharge station (I; II). According to the invention, at a delivery device (03) level upstream of a lateral inlet in the stacking space of the upstream second discharge station (II; I), at least one operator interface (232; 253) with at least one actuating means (196'; 197'; 198'; 199'; 211'; 212'; 213'; 214'; 216; 217; 218; 219; 221; 222; 223; 224; 226; 227 228; 229; 231; 233; 234; 235; 236; 237; 238; 240; 241; 242) is provided which is permanently connected to the signal or can be activated by means of an additional actuating means (245; 246; 247) with the control element (63; 06; 124; 147; 202) of the at least one format-or transport-relevant device (48; 49; 51; 52; 103; 139) of the first discharge station (I; II) and which allows or can allow, during actuation, the control element (63; 106; 124; 147; 202) of the system (48; 49; 1; 52; 103; 139) of the first discharge station (I; II) which can vary with regard to a format-or transport-relevant size variable, to be controlled.

IPC 8 full level

**B41F 13/70** (2006.01); **B65H 29/04** (2006.01); **B65H 29/24** (2006.01); **B65H 29/68** (2006.01); **B65H 31/20** (2006.01); **B65H 31/24** (2006.01); **B65H 43/00** (2006.01)

CPC (source: CN EP US)

**B41F 13/70** (2013.01 - CN EP US); **B65H 29/041** (2013.01 - CN EP US); **B65H 29/047** (2013.01 - CN EP US); **B65H 29/247** (2013.01 - CN EP US); **B65H 29/683** (2013.01 - CN EP US); **B65H 31/20** (2013.01 - CN EP US); **B65H 31/24** (2013.01 - CN EP US); **B65H 43/00** (2013.01 - CN EP US); **B65H 2405/114** (2013.01 - CN EP US); **B65H 2405/3311** (2013.01 - CN EP US); **B65H 2405/58** (2013.01 - CN EP US); **B65H 2406/122** (2013.01 - CN EP US); **B65H 2511/12** (2013.01 - CN EP US); **B65H 2511/20** (2013.01 - CN EP US); **B65H 2513/10** (2013.01 - CN EP US); **B65H 2515/34** (2013.01 - CN EP US); **B65H 2551/18** (2013.01 - CN EP US); **B65H 2553/42** (2013.01 - CN EP US); **B65H 2801/21** (2013.01 - CN EP US)

Citation (examination)

DE 19819490 C1 19991028 - ROLAND MAN DRUCKMASCH [DE]

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**WO 2017001394 A2 20170105**; **WO 2017001394 A3 20170316**; CN 107771127 A 20180306; CN 107771127 B 20190308; EP 3271174 A2 20180124; EP 3271174 B1 20200311; US 10150644 B2 20181211; US 2018148295 A1 20180531

DOCDB simple family (application)

**EP 2016064996 W 20160628**; CN 201680028819 A 20160628; EP 16733072 A 20160628; US 201615574645 A 20160628