

Title (en)

OPERATING DEVICE FOR A TILT AND TURN DOOR OR WINDOW

Title (de)

BETRIEBSVORRICHTUNG FÜR KIPPBARE UND DREHBARE TÜR ODER FENSTER

Title (fr)

DISPOSITIF DE COMMANDE POUR UNE PORTE OU UNE FENÊTRE OSCILLO-BATTANTE

Publication

EP 3274535 B1 20200930 (EN)

Application

EP 16716694 A 20160322

Priority

- IT BO20150150 A 20150327
- IB 2016051598 W 20160322

Abstract (en)

[origin: WO2016157024A1] Described is an operating device for a tilt and turn door or window (1) comprising a fixed frame (2) and a movable sash (3) connected to each other along a corresponding vertical upright (4, 5) by a pair of hinges, a lower hinge (6) and an upper hinge (7), and a control handle (8) positioned on the upright (9) of the sash (3) opposite to that connected to the fixed frame (2); the operating device (100) comprises a slider (10) for transmitting the movement of the handle (8) housed and slidable inside a groove (11) of an upper crosspiece (12) of the sash (3); a positioning body (13) fixed in the groove (11) of the upper crosspiece (12); the body (13) has a slot (14) with a longitudinal operating extension (L); a connecting arm (15) articulated, at a first end, to the movable portion of the upper hinge (7) and, at the other end, to the positioning body (13) by means of a pin (16) housed in the slot (14) of the positioning body (13); the arm (15) has a relative surface provided with two elements (17, 18) protruding towards the groove (11) and a free zone (19), spaced from each other along the arm (15); a selector element (20) connected to the slider (10), slidable inside the groove (11) of the upper crosspiece (12) for intercepting, according to a sequence predetermined by the relative position of the protruding elements (17, 18) and the free zone (19), the protruding elements (17, 18) and free zone (19), in such a way as to define corresponding closed, turning opening and tilted open configurations which can be adopted by the movable sash (3), the device (100) comprising means (32) for adjusting the stroke of the pin (16) of the connecting arm (15) inside the slot (14) of the positioning body (13); the adjusting means (32) being positioned on the positioning body (13) and movable between several stable positions inside the slot (14) for modifying the longitudinal operating extension (L).

IPC 8 full level

E05D 15/52 (2006.01); **E05D 15/30** (2006.01)

CPC (source: CN EP)

E05D 15/5205 (2013.01 - CN EP); **E05D 15/5217** (2013.01 - CN EP); **E05D 15/30** (2013.01 - EP); **E05Y 2201/22** (2013.01 - EP); **E05Y 2600/10** (2013.01 - EP); **E05Y 2600/12** (2013.01 - EP); **E05Y 2600/14** (2013.01 - EP); **E05Y 2600/312** (2013.01 - EP); **E05Y 2600/33** (2013.01 - EP); **E05Y 2800/17** (2013.01 - EP); **E05Y 2900/148** (2013.01 - EP)

Cited by

EP4187049A1; EP4187050A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2016157024 A1 20161006; CN 107454921 A 20171208; CN 107454921 B 20191108; CN 110359800 A 20191022; CN 110359800 B 20210409; EP 3274535 A1 20180131; EP 3274535 B1 20200930; ES 2834798 T3 20210618; PT 3274535 T 20201215

DOCDB simple family (application)

IB 2016051598 W 20160322; CN 201680018646 A 20160322; CN 201910653300 A 20160322; EP 16716694 A 20160322; ES 16716694 T 20160322; PT 16716694 T 20160322