

Title (en)

GUIDE VANE ADJUSTMENT DEVICE AND TURBOMACHINE

Title (de)

LEITSCHAUFELVERSTELLVORRICHTUNG UND STRÖMUNGSMASCHINE

Title (fr)

DISPOSITIF DE RÉGLAGE D'AUBES DIRECTRICES ET TURBOMACHINE

Publication

EP 3283732 B1 20200729 (DE)

Application

EP 16716553 A 20160414

Priority

- DE 102015004648 A 20150415
- EP 2016058181 W 20160414

Abstract (en)

[origin: WO2016166191A2] The invention relates to a guide vane adjustment device for a turbomachine, namely for rotating a plurality of guide vanes, arranged in groups to give a vane ring, about a guide vane axis that runs in a radial direction of a rotor of the turbomachine. Said guide vane adjustment device comprises a driveshaft (26) to which a drive motor can be coupled and which can be driven by the drive motor; and a control ring (27) that transmits a rotation of the driveshaft (26) onto the guide vanes (21) of the vane ring (20) in order to rotate said guide vanes. The driveshaft (26) is directly coupled to one of the guide vanes (21) of the vane ring (20) such that said guide vane of the vane ring can be directly rotated without interposition of the control ring (27), starting from the driveshaft (26); The driveshaft (26) or the guide vane (21) that can be directly driven by the driveshaft (26) is coupled to the control ring (27) via a transmission lever (28) in an articulated manner. The driveshaft (26) is indirectly coupled to the other guide vanes (21) of the vane ring (20) such that the other guide vanes of the vane ring can be indirectly rotated with the interposition of the control ring (27), starting from the driveshaft (26). The guide vanes (21) that can be indirectly driven by the driveshaft (26) are coupled to the control ring (27) via additional transmission levers (29) in an articulated manner. The control ring (27) can be moved in the circumferential direction and in the axial direction so that forces on the coupling points between the control ring (27) and the transmission levers (28, 29) that are coupled to the control ring (27) in an articulated manner run perpendicular to the transmission levers (28, 29).

IPC 8 full level

F01D 17/00 (2006.01); **F01D 17/16** (2006.01); **F04D 29/56** (2006.01)

CPC (source: CN EP KR RU US)

F01D 9/02 (2013.01 - CN); **F01D 9/04** (2013.01 - RU); **F01D 9/041** (2013.01 - US); **F01D 17/00** (2013.01 - EP RU US);
F01D 17/162 (2013.01 - EP KR US); **F01D 17/167** (2013.01 - EP US); **F03B 3/183** (2013.01 - CN); **F04D 29/46** (2013.01 - CN);
F04D 29/56 (2013.01 - CN); **F04D 29/563** (2013.01 - EP KR US); **F04D 29/566** (2013.01 - EP KR US); **F01D 5/02** (2013.01 - US);
F05D 2260/50 (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102015004648 A1 20161020; CN 107429572 A 20171201; CN 107429572 B 20200306; EP 3283732 A2 20180221;
EP 3283732 B1 20200729; JP 2018511735 A 20180426; JP 6683730 B2 20200422; KR 20170136632 A 20171211; RU 2675948 C1 20181225;
US 10774673 B2 20200915; US 2018100407 A1 20180412; WO 2016166191 A2 20161020; WO 2016166191 A3 20170126;
WO 2016166191 A4 20170316

DOCDB simple family (application)

DE 102015004648 A 20150415; CN 201680021800 A 20160414; EP 16716553 A 20160414; EP 2016058181 W 20160414;
JP 2017553951 A 20160414; KR 20177032955 A 20160414; RU 2017139321 A 20160414; US 201615566483 A 20160414