

Title (en)

WEB MEANDERING CONTROL DEVICE AND CONTROL METHOD

Title (de)

SCHLÄNGELUNGSSTEUERUNGSVORRICHTUNG UND -STEUERUNGSVERFAHREN FÜR GEWEBE

Title (fr)

DISPOSITIF DE COMMANDE ET PROCÉDÉ DE COMMANDE DE MÉANDRES DE FILM

Publication

**EP 3315440 A4 20190417 (EN)**

Application

**EP 15896344 A 20150625**

Priority

JP 2015068287 W 20150625

Abstract (en)

[origin: EP3315440A1] In the present invention, a web end (1 E), which is an end in the width direction perpendicular to the travel direction of a web (1), and a pattern end (1A1), which is an end in the width direction of each pattern (1A) repeatedly printed along the travel direction on the web (1), are detected at a first position in the web travel direction. A web end detection signal (G1) representative of the detected web end (1 E) and a picture end detection signal (G2) representative of the detected pattern end (1A1) are captured, and a control signal for aligning the pattern end (1A1) with a preset picture end reference position (P1) is generated. The web is moved in the width direction by the control signal.

IPC 8 full level

**B65H 23/032** (2006.01); **B65H 23/02** (2006.01)

CPC (source: EP)

**B65H 23/0216** (2013.01); **B65H 23/032** (2013.01); **B65H 2511/00** (2013.01)

Citation (search report)

- [XAI] US 4848632 A 19890718 - MACK HORST [DE], et al
- See references of WO 2016208022A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 3315440 A1 20180502**; **EP 3315440 A4 20190417**; **EP 3315440 B1 20201014**; JP 5851671 B1 20160203; JP WO2016208022 A1 20170622; TW 201704917 A 20170201; TW I707217 B 20201011; WO 2016208022 A1 20161229

DOCDB simple family (application)

**EP 15896344 A 20150625**; JP 2015068287 W 20150625; JP 2015550511 A 20150625; TW 105105656 A 20160225