

Title (en)
PRINT AGGREGATE

Title (de)
DRUCKAGGREGAT

Title (fr)
AGRÉGAT D'IMPRESSION

Publication
EP 3337659 A1 20180627 (DE)

Application
EP 16751250 A 20160804

Priority
• DE 102015215723 A 20150818
• EP 2016068602 W 20160804

Abstract (en)
[origin: WO2017029115A1] The invention relates to a printing assembly (200), wherein the printing assembly (200) has at least one frame (283), which has at least two side walls (271), between which a transport path provided for the transport of printing material (02) at least partially extends, and wherein at least one transport direction is defined by the transport path provided for the transport of printing material (02) and wherein the printing assembly (200) has at least two crossmembers (272), which are spaced apart from each other in the transport direction and which each extend from one of the side walls (271) to another of the side walls (271), and wherein each of the at least two crossmembers (272) has at least one first crossbeam (611) and at least one second crossbeam (612) spaced apart therefrom, which jointly bound at least one interior of the particular crossmember (272) at least partially in and against the transport direction, and wherein at least one component of a gas transport device and/or at least one additional device (247; 263; 601; 602; 603; 604; 607; 608) for supplying at least one printing head (221) with energy and/or operating media and/or printing fluid and/or data and/or at least one gas and/or at least one inner additional device (247; 263; 601; 602; 603; 604; 607; 608) for cleaning and/or maintaining and/or covering at least one printing head (221) is arranged in the at least one interior in each case and wherein the printing assembly (200) has at least one supporting body (616), which can be moved in relation to the frame (283) in at least one parking direction (C) and which extends at least in a transverse direction (A) between the side walls (271), and wherein at least one printing head (221) is arranged on the at least one supporting body (616) and can be moved jointly with the at least one supporting body (616).

IPC 8 full level
B41J 2/215 (2006.01); **B41J 2/155** (2006.01); **B41J 2/165** (2006.01); **B41J 13/00** (2006.01); **B41J 25/304** (2006.01); **B41J 25/308** (2006.01); **B41J 29/377** (2006.01)

CPC (source: EP US)
B41J 2/155 (2013.01 - EP US); **B41J 2/16552** (2013.01 - EP US); **B41J 2/16585** (2013.01 - EP US); **B41J 2/215** (2013.01 - US); **B41J 13/00** (2013.01 - US); **B41J 25/304** (2013.01 - US); **B41J 25/308** (2013.01 - US); **B41J 25/3088** (2013.01 - US); **B41J 29/377** (2013.01 - EP US); **B41J 2002/16555** (2013.01 - EP US)

Citation (search report)
See references of WO 2017029115A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
DE 102015215723 A1 20170223; CN 107921779 A 20180417; CN 107921779 B 20190426; EP 3337659 A1 20180627; EP 3337659 B1 20200311; JP 2018528099 A 20180927; JP 6440899 B2 20181219; US 10131149 B2 20181120; US 2018250939 A1 20180906; WO 2017029115 A1 20170223

DOCDB simple family (application)
DE 102015215723 A 20150818; CN 201680047099 A 20160804; EP 16751250 A 20160804; EP 2016068602 W 20160804; JP 2018508655 A 20160804; US 201615752656 A 20160804