

Title (en)

SYSTEM AND FASTENING POINT FOR THE SCREWLESS FASTENING OF A RAIL FOR A RAIL VEHICLE

Title (de)

SYSTEM UND BEFESTIGUNGSPUNKT ZUM SCHRAUBENLOSEN BEFESTIGEN EINER SCHIENE FÜR EIN SCHIENENFAHRZEUG

Title (fr)

SYSTÈME ET POINT DE FIXATION PERMETTANT LA FIXATION SANS VIS D'UN RAIL POUR UN VÉHICULE FERROVIAIRE

Publication

EP 3356599 A1 20180808 (DE)

Application

EP 16757918 A 20160831

Priority

- DE 102015116345 A 20150928
- EP 2016070471 W 20160831

Abstract (en)

[origin: WO2017054998A1] The invention provides a system for screwless rail fastening and a corresponding fastening point on an underlying surface, which are easy to assemble and ensure optimal secure fastening with maximum load capacity and under hard usage conditions. For this purpose, such a system comprises a spring element (4), which is bent from a spring wire, and a support shoulder (2). In succession from one end of the spring element, the spring element (4) comprises a support segment (4a), a curve segment (4b), a hold-down segment (4c), which is oriented opposite to the support segment (4a), a curve segment (4d), which is curved in the direction of the support segment (4a), and a locking segment (4e), which is oriented transversely with respect to the support segment (4a). When the spring element (4) is not mounted, there is a distance (a) between the hold-down segment (4c) and the locking segment (4e) when viewed from the side. At the same time, the support shoulder (2) comprises a fastening segment for holding the support shoulder (2) on the underlying surface (U), a carrier segment (2a) supported by the fastening segment, a support hole (2f) formed on the carrier segment (2a) for pivotably supporting the support segment (4a) about a pivot axis, and a locking head (2b), which is supported by the carrier segment (2a) and on which an abutment (2i) for the locking segment (4e) is formed in such a way that, when the system (1) is fully assembled, the locking segment (4e) is held in a position relative to the support segment (4a) of the spring element (4) in which the spring element (4) is resiliently loaded between the support hole (2f) and the abutment (2i) of the support shoulder (2) and the hold-down segment (4c) acts resiliently against the surface of the rail foot (F) that is associated with the hold-down segment.

IPC 8 full level

E01B 9/30 (2006.01); **E01B 9/34** (2006.01); **E01B 9/48** (2006.01)

CPC (source: EP US)

E01B 9/303 (2013.01 - EP US); **E01B 9/48** (2013.01 - EP); **E01B 9/483** (2013.01 - EP US); **E01B 9/60** (2013.01 - US); **E01B 9/62** (2013.01 - US); **E01B 29/24** (2013.01 - US); **E01B 9/34** (2013.01 - EP US); **E01B 2201/00** (2013.01 - US); **E01B 2205/00** (2013.01 - EP US)

Citation (search report)

See references of WO 2017054998A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 202015106541 U1 20161229; CN 108138449 A 20180608; CN 108138449 B 20191213; DE 102015116345 B3 20170330; EA 036462 B1 20201112; EA 201890387 A1 20180831; EP 3356599 A1 20180808; EP 3356599 B1 20191030; PL 3356599 T3 20200518; US 10472772 B2 20191112; US 2018274177 A1 20180927; WO 2017054998 A1 20170406

DOCDB simple family (application)

DE 202015106541 U 20150928; CN 201680056455 A 20160831; DE 102015116345 A 20150928; EA 201890387 A 20160831; EP 16757918 A 20160831; EP 2016070471 W 20160831; PL 16757918 T 20160831; US 201615761489 A 20160831