

Title (en)  
GLOW PLUG

Title (de)  
GLÜHKERZE

Title (fr)  
BOUGIE DE PRÉCHAUFFAGE

Publication  
**EP 3358257 B1 20191120 (EN)**

Application  
**EP 18151698 A 20180115**

Priority  
JP 2017018307 A 20170203

Abstract (en)  
[origin: EP3358257A1] To provide a glow plug capable of restraining a temperature drop in the event of lowering applied voltage for saturating temperature, while ensuring durability and provision of higher heating-up temperature. A rearward coil connected to the rear end of a forward coil containing W or Mo as a main component has a resistance ratio R1 lower than a resistance ratio R2 of the forward coil, where the resistance ratio R1 is the ratio of the resistance of the rearward coil at 1,000°C to the resistance of the rearward coil at 20°C, and the resistance ratio R2 is the ratio of the resistance of the forward coil at 1,000°C to the resistance of the forward coil at 20°C. A tube has a tube forward portion ranging from the forward end of the tube to a position around the axial center of the forward coil and a tube rearward portion ranging from a position around the rear end of the rearward coil to a position around the forward end of the rearward coil. The wall thickness A of the tube forward portion is 0.5 mm or more; the wall thickness B of the tube rearward portion is 0.3 mm or more; and the minimal wall thickness B1 of the tube rearward portion is smaller than the wall thickness A of the tube forward portion.

IPC 8 full level  
**F23Q 7/00** (2006.01)

CPC (source: EP)  
**F23Q 7/001** (2013.01)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 3358257 A1 20180808; EP 3358257 B1 20191120**; JP 2018124030 A 20180809; JP 6996848 B2 20220117

DOCDB simple family (application)  
**EP 18151698 A 20180115**; JP 2017018307 A 20170203