

Title (en)  
THRUST COLLAR

Title (de)  
DRUCKRING

Title (fr)  
COLLET DE BUTÉE

Publication  
**EP 3359313 A1 20180815 (EN)**

Application  
**EP 16781848 A 20161007**

Priority  
• GB 201517771 A 20151008  
• GB 2016053135 W 20161007

Abstract (en)  
[origin: WO2017060730A1] A thrust collar is provided for preventing and limiting the axial movement of a rotating shaft and/or related bearing arrangement, principally in heavy engineering applications. The thrust collar (10) comprises first and second generally semi-circular body members (12,14), each body member having a first end (16) and a second end (20). A hinge arrangement pivotably connects the first ends (16) of the body members (12,14) to one another. The collar also includes a locking mechanism which has a locking member (40), and a locking rod (44) having a first rod end (46) pivotably attached to the second end (20) of the first body member (12), and a second rod end (50) pivotably attached to the locking member (40). A locking recess (42) is located adjacent the second end (20) of the second body member (14), with the locking member (40) being engageable in the locking recess so as to lock the second ends of the first and second body members (12,14) together.

IPC 8 full level  
**B21B 31/07** (2006.01); **F16B 2/10** (2006.01); **F16B 2/18** (2006.01); **F16C 13/02** (2006.01); **F16C 35/063** (2006.01)

CPC (source: EP)  
**F16B 2/10** (2013.01); **F16B 2/185** (2013.01); **B21B 31/07** (2013.01); **F16C 13/02** (2013.01); **F16C 35/063** (2013.01); **F16C 2208/60** (2013.01);  
**F16C 2220/02** (2013.01); **F16C 2226/74** (2013.01)

Citation (search report)  
See references of WO 2017060730A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**WO 2017060730 A1 20170413**; EP 3359313 A1 20180815; GB 201517771 D0 20151125

DOCDB simple family (application)  
**GB 2016053135 W 20161007**; EP 16781848 A 20161007; GB 201517771 A 20151008