

Title (en)
LIFTING SYSTEM AND METHOD FOR LIFTING AND/OR LOWERING LOADS

Title (de)
HUBSYSTEM UND VERFAHREN ZUM ANHEBEN UND/ODER ABSSENKEN VON LASTEN

Title (fr)
SYSTÈME DE LEVAGE ET PROCÉDÉ DE LEVAGE ET/OU D'ABAISSEMENT DE CHARGES

Publication
EP 3371092 A1 20180912 (DE)

Application
EP 16790388 A 20161103

Priority
• DE 102015014280 A 20151106
• EP 2016076605 W 20161103

Abstract (en)
[origin: WO2017077000A1] The invention relates to a lifting system (100, 200) for lifting and/or lowering loads (102, 202), having: a) a lifting apparatus (104, 204) which is suitable for conveying loads (102, 202) along a lifting direction (106, 206) from a first transfer position (108) into a second transfer position (110) and along a lowering direction (112, 212) from the second transfer position (110) to the first transfer position (108), and b) a conveyor apparatus (120, 220) which is suitable for taking on, at the first and/or the second transfer position (108, 110), the loads (102, 202) conveyed by means of the lifting apparatus (104, 204), c) wherein the conveyor apparatus (120, 220) has at least one holding pendulum (300) which is pivotable into a holding position, d) wherein the lifting apparatus (104, 204) has at least one holding receptacle (400, 500, 600) for the holding pendulum (300), e) wherein the holding pendulum (300), in the holding position, can be placed in engagement with the holding receptacle (400, 500, 600), by means of a movement of the holding receptacle (400, 500, 600) in the lowering direction (112, 212), such that a movement of the lifting apparatus (104, 204) in the lowering direction (112, 212) is blocked, and/or the holding pendulum (300), in the holding position, can be placed in engagement with the holding receptacle (400, 500, 600), by means of a movement of the holding receptacle (400, 500, 600) in the lifting direction (106, 206), in such a way that a movement of the lifting apparatus (104, 204) in the lifting direction (106, 206) is blocked, f) wherein the holding receptacle (400, 500, 600) has a first guide track (404, 502, 610), g) wherein the first guide track (404, 502, 610) is designed so as, during a movement of the holding receptacle (400, 500, 600) along the lifting direction (106, 206) or the lowering direction (112, 212), to move the holding pendulum (300) into a first position in which the holding pendulum (300) cannot be placed in engagement with the holding receptacle (400, 500, 600). The invention also relates to a method for blocking and releasing a lifting apparatus of a lifting system.

IPC 8 full level
B66F 7/00 (2006.01); **B66F 9/00** (2006.01); **B66F 17/00** (2006.01)

CPC (source: EP US)
B66F 7/00 (2013.01 - EP US); **B66F 9/00** (2013.01 - EP US); **B66F 9/02** (2013.01 - US); **B66F 17/00** (2013.01 - EP US)

Citation (search report)
See references of WO 2017077000A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2017077000 A1 20170511; CN 108349717 A 20180731; CN 108349717 B 20191231; DE 102015014280 A1 20170511;
EP 3371092 A1 20180912; EP 3371092 B1 20210526; PL 3371092 T3 20211122; US 10556784 B2 20200211; US 2018319645 A1 20181108

DOCDB simple family (application)
EP 2016076605 W 20161103; CN 201680064724 A 20161103; DE 102015014280 A 20151106; EP 16790388 A 20161103;
PL 16790388 T 20161103; US 201615773267 A 20161103