

Title (en)

SOLENOID VALVE FOR A FUEL INJECTION VALVE, METHOD FOR OPERATING THE SOLENOID VALVE, AND FUEL INJECTION VALVE HAVING A SOLENOID VALVE OF SAID TYPE

Title (de)

MAGNETVENTIL FÜR EIN KRAFTSTOFFEINSPRITZVENTIL, VERFAHREN ZUM BETREIBEN DES MAGNETVENTILS UND KRAFTSTOFFEINSPRITZVENTIL MIT EINEM SOLCHEN MAGNETVENTIL

Title (fr)

ÉLECTROVALVE POUR UNE SOUPAPE D'INJECTION DE CARBURANT, PROCÉDÉ DE FONCTIONNEMENT DE L'ÉLECTROVALVE ET SOUPAPE D'INJECTION DE CARBURANT COMPRENNANT UNE TELLE ÉLECTROVALVE

Publication

**EP 3394420 B1 20200506 (DE)**

Application

**EP 16798522 A 20161122**

Priority

- DE 102015226499 A 20151222
- EP 2016078375 W 20161122

Abstract (en)

[origin: WO2017108297A1] A solenoid valve for a fuel injection valve, having a magnet armature (40) which has a longitudinal axis (3) and which is movable along said longitudinal axis (3) and which interacts with an electromagnet (44), wherein the magnet armature (40) forms an armature plate (140) which is arranged opposite the electromagnet (44). Between the electromagnet (44) and the armature plate (140), a residual air gap disc (52) prevents direct abutment of the armature plate (140) against the electromagnet (44), wherein the armature plate (140) comes into contact by means of its outer edge with the residual air gap disc (52). A closing spring (50) subjects the magnet armature (40) to a closing force in the direction of a valve seat (42), wherein the closing spring (50) lies against the armature plate (140) close to the longitudinal axis (3) thereof. By means of the interaction of the magnet armature (40) with the valve seat (42), a throughflow cross section for a fluid can be opened or closed. A weakening zone (55) is formed radially within the armature plate (140). In a method for operating the solenoid valve, in the presence of a low temperature of the solenoid valve, a first coil current is conducted through the electromagnet (44), whereby a magnetic force is generated which exceeds the level required for a movement of the magnet armature and for overcoming the force of the closing spring (50). In the presence of a higher temperature, the coil current for opening the solenoid valve is reduced in relation to the first coil current.

IPC 8 full level

**F02M 51/06** (2006.01); **F02D 41/06** (2006.01); **F02M 61/16** (2006.01); **F02M 63/00** (2006.01); **F16K 31/06** (2006.01); **H01F 7/08** (2006.01); **H01F 7/16** (2006.01)

CPC (source: EP KR)

**F02D 41/064** (2013.01 - EP KR); **F02D 41/20** (2013.01 - EP KR); **F02M 51/0635** (2013.01 - EP KR); **F02M 61/167** (2013.01 - EP KR); **F02M 63/0017** (2013.01 - KR); **H01F 7/1638** (2013.01 - EP KR); **F02D 2041/2065** (2013.01 - EP KR); **F02M 63/0017** (2013.01 - EP); **F02M 2200/26** (2013.01 - EP KR); **H01F 2007/086** (2013.01 - EP KR); **H01F 2007/1661** (2013.01 - EP KR)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**DE 102015226499 A1 20170622**; EP 3394420 A1 20181031; EP 3394420 B1 20200506; KR 20180094093 A 20180822; WO 2017108297 A1 20170629

DOCDB simple family (application)

**DE 102015226499 A 20151222**; EP 16798522 A 20161122; EP 2016078375 W 20161122; KR 20187020487 A 20161122