

Title (en)
VALVE ARMATURE FOR THE FILLING OF A SANITARY CISTERN AND SANITARY CISTERN HAVING A VALVE ARMATURE OF THIS TYPE

Title (de)
VENTILARMATUR FÜR DIE BEFÜLLUNG EINES SANITÄREN SPÜLKASTENS UND SANITÄRER SPÜLKASTEN MIT EINER SOLCHEN VENTILARMATUR

Title (fr)
ROBINETTERIE À SOUPAPE SERVANT À REMPLIR UN RÉSERVOIR DE CHASSE SANITAIRE ET RÉSERVOIR DE CHASSE SANITAIRE MUNI DE LADITE ROBINETTERIE À SOUPAPE

Publication
EP 3400342 B1 20210120 (DE)

Application
EP 16822178 A 20161223

Priority
• DE 202016000056 U 20160107
• EP 2016082532 W 20161223

Abstract (en)
[origin: WO2017118583A1] The invention relates to a valve armature (1) for the filling of a sanitary cistern (9), in particular a concealed cistern, comprising a connection element (2) for connecting the valve armature to a water supply line, a blocking valve (3) having an actuation element (4) for manually blocking the supply flow from the water supply line, and a float-actuated filling valve (5), wherein the connection element (2), the blocking valve (3) and the filling valve (5) can be detachably connected to one another to form a stretch of water, such that water can be supplied from the water supply line into the internal space of the cistern (9), and wherein a float (6) connected to the filling valve can be moved by an increasing water level in the cistern, and the filling valve closes when a predetermined or predeterminable water level is reached, thereby interrupting the supply via the stretch of water. The valve armature (1) according to the invention is characterised in that the actuation element (4) of the blocking valve (3) can be rotated about a substantially horizontal axis of rotation (M) in the functional position of the float (6), wherein the blocking valve (3) is configured such that it can be deployed functionally in the valve armature (1) in at least two different positions, wherein the connection element (2) is/can be mounted in an opening (8) in the left lateral wall (9.1) of the cistern in one of the positions, and in an opening (8') in the right lateral wall (9.2) of the cistern in another of the positions, and wherein the actuation element (4) is accessible from the front side of the valve armature in the at least two positions of the blocking valve (3). The invention also relates to a sanitary cistern (9) having a valve armature (1) of this type.

IPC 8 full level
E03C 1/02 (2006.01); **E03D 1/012** (2006.01); **E03D 1/32** (2006.01)

CPC (source: EP US)
E03C 1/021 (2013.01 - EP US); **E03D 1/32** (2013.01 - EP US); **E03D 1/33** (2013.01 - US); **F16K 31/26** (2013.01 - US); **F16K 31/602** (2013.01 - US); **E03D 1/0125** (2013.01 - EP US); **Y10T 137/7368** (2015.04 - US)

Cited by
EP3900530A1; WO2021213824A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 202016000056 U1 20170410; AU 2016384266 A1 20180531; AU 2016384266 B2 20190718; CN 108603367 A 20180928; CN 108603367 B 20200324; EP 3400342 A1 20181114; EP 3400342 B1 20210120; ES 2849430 T3 20210818; PL 3400342 T3 20210517; US 10570597 B2 20200225; US 2018371731 A1 20181227; WO 2017118583 A1 20170713

DOCDB simple family (application)
DE 202016000056 U 20160107; AU 2016384266 A 20161223; CN 201680078213 A 20161223; EP 16822178 A 20161223; EP 2016082532 W 20161223; ES 16822178 T 20161223; PL 16822178 T 20161223; US 201615781834 A 20161223