

Title (en)
VALVE GUN FOR A HIGH-PRESSURE CLEANING DEVICE

Title (de)
VENTILPISTOLE FÜR EIN HOCHDRUCKREINIGUNGSGERÄT

Title (fr)
PISTOLET À SOUPAPE POUR UN NETTOYEUR HAUTE PRESSION

Publication
EP 3433023 A1 20190130 (DE)

Application
EP 16711822 A 20160323

Priority
EP 2016056391 W 20160323

Abstract (en)
[origin: WO2017162282A1] The invention relates to a valve gun for a high-pressure cleaning device comprising a valve (24) which has a closing body (42) which is arranged on a valve tappet (44) and in a closed position rests tightly against a valve seat (40) and which is movable into an open position spaced apart from the valve seat (40) by pivoting of a trigger lever (52; 202) mounted pivotably about a first pivot axis (66). In the closed position of the closing body (42) the trigger lever (52; 202) adopts a rest position and in the open position of the closing body (42) the trigger lever adopts a release position and is mechanically coupled to the valve tappet (44) by means of a coupling lever (54; 216) mounted pivotably about a second pivot axis (86). A pivoting movement of the trigger lever (52; 202) can be transmitted to the coupling lever (54; 216) by means of a coupling member (74; 154; 208; 260) which is movable along a guide track (94; 152; 212; 252), and the guide track (94; 152; 212; 252) has a first end portion (96; 160; 218; 254), an intermediate portion (98; 162; 220; 256) and a second end portion (100; 164; 222; 258). In order to modify the valve gun in such a way that the valve gun has a simpler design in structural terms and nevertheless can be actuated by the user in a simple manner, the coupling member (74; 154; 208; 260) is movable during pivoting of the trigger lever (52; 202) from the rest position to the release position along the first end portion (96; 160; 218; 254), then along the intermediate portion (98; 162; 220; 256) and subsequently along the second end portion (100; 164; 222; 258), and the first end portion (96; 160; 218; 254) has a lesser inclination with respect to the pivoting direction of the trigger lever (52; 202) than the intermediate portion (98; 162; 220; 256).

IPC 8 full level
B05B 1/30 (2006.01); **B05B 9/01** (2006.01); **B05B 12/00** (2018.01); **B08B 3/02** (2006.01); **G05G 7/04** (2006.01)

CPC (source: EP US)
B05B 1/3013 (2013.01 - EP); **B05B 9/01** (2013.01 - EP); **B05B 12/002** (2013.01 - EP US); **B08B 3/028** (2013.01 - EP)

Citation (search report)
See references of WO 2017162282A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2017162282 A1 20170928; CN 108698055 A 20181023; CN 108698055 B 20211210; DK 3433023 T3 20210503; EP 3433023 A1 20190130; EP 3433023 B1 20210317

DOCDB simple family (application)
EP 2016056391 W 20160323; CN 201680078919 A 20160323; DK 16711822 T 20160323; EP 16711822 A 20160323