Title (en)

## DISPENSING APPARATUS

Title (de)

AUSGABEVORRICHTUNG

Title (fr)

DISPOSITIF DE DISTRIBUTION

Publication

## EP 3433461 B1 20190807 (DE)

Application

## EP 18700664 A 20180115

Priority

- DE 102017104191 A 20170228
- EP 2018050878 W 20180115

Abstract (en)

[origin: WO2018157987A1] The present invention relates to a dispensing apparatus (10) for unpackaged goods, in particular baked goods such as bread, rolls or the like, having at least one carrier framework (12) and having at least one drawer-like insert (14), which in the installed state is inserted into the carrier framework (12), wherein the drawer-like insert (14) surrounds a goods-accommodating space (16), which contains at least one tray-like and/or board-like holder (18) for the goods, and wherein the drawer-like insert (14) has at least one front opening (22), via which the goods-accommodating space (16) and the tray-like and/or board-like holder (18) are accessible, and wherein the drawer-like insert (14) has at least one transparent door (24) and at least one door guide (28), which is arranged in the upper region of the opening (22), as seen in the installed and set-up state of the dispensing apparatus (10), wherein the door (24) has at least two guide pins (30) and wherein the door (24) can be pushed at least to some extent into the goods-accommodating space (16), wherein the door (24), in which the guide pins (30) are guided such that the door (24) can be pushed at least to some extent into the goods-accommodating space (16), wherein the first guide aperture (32) runs substantially vertically, as seen in relation to the installed and set-up state of the dispensing apparatus (10), and wherein the first guide aperture (34) runs substantially horizontally and substantially rectilinearly, as seen in relation to the installed and set-up state of the dispensing apparatus (10), and wherein the second guide aperture (34) runs substantially horizontally and substantially rectilinearly, as seen in relation to the installed and set-up state of the dispensing apparatus (10), and wherein the second guide aperture (34) runs substantially horizontally and substantially rectilinearly, as seen in relation to the installed and set-up state of the dispensing apparatus (10), that, when in the pushed-in state, the door (

IPC 8 full level

E06B 3/50 (2006.01); A47G 19/32 (2006.01); G07F 11/62 (2006.01)

CPC (source: EP) A47G 19/32 (2013.01); G07F 11/62 (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**DE 102017104191 A1 20180830**; AU 2018229381 A1 20190808; EP 3433461 A1 20190130; EP 3433461 B1 20190807; ES 2744809 T3 20200226; WO 2018157987 A1 20180907

DOCDB simple family (application)

**DE 102017104191 A 20170228**; AU 2018229381 A 20180115; EP 18700664 A 20180115; EP 2018050878 W 20180115; ES 18700664 T 20180115