

Title (en)

METHOD AND APPARATUS FOR EJECTING A HELICALLY WOUND PIPE FROM A MANDREL

Title (de)

VERFAHREN UND VORRICHTUNG ZUM AUSSTOSSEN EINES SCHRAUBENFÖRMIG GEWICKELTEN ROHRS AUS EINEM DORN

Title (fr)

PROCÉDÉ ET APPAREIL D'ÉJECTION D'UN TUBE ENROULÉ DE FAÇON HÉLICOÏDALE D'UN MANDRIN

Publication

EP 3453518 B1 20231108 (EN)

Application

EP 17190115 A 20170908

Priority

EP 17190115 A 20170908

Abstract (en)

[origin: EP3453518A1] According to the present invention, there is provided a method and an apparatus for ejecting a helically wound pipe section from a mandrel (5), wherein the mandrel (5) has a longitudinal axis around which it is rotated and a cylindrical outer surface around which the profile forming the pipe section is wound. The method comprises steps of cutting the profile that is wound on the mandrel (5) to form an end of the pipe section, pushing at least one ejector element against the end of the pipe section, holding the at least one ejector element stationary in the direction of the longitudinal axis of the mandrel (5) and rotating the mandrel (5) and pipe section in the same direction as the profile is wound on the mandrel.

IPC 8 full level

B29C 53/82 (2006.01); **B29C 33/44** (2006.01); **B29C 37/00** (2006.01); **B29C 53/62** (2006.01); **B29C 53/78** (2006.01); **B29C 53/80** (2006.01)

CPC (source: EP)

B29C 37/0021 (2013.01); **B29C 53/821** (2013.01); **B29C 53/62** (2013.01); **B29C 53/78** (2013.01); **B29C 53/8041** (2013.01)

Cited by

CN112829335A

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3453518 A1 20190313; **EP 3453518 B1 20231108**; **EP 3453518 C0 20231108**; AR 113045 A1 20200122; ES 2965963 T3 20240417; HR P20240138 T1 20240412; PL 3453518 T3 20240402; RS 65108 B1 20240229; WO 2019048741 A1 20190314

DOCDB simple family (application)

EP 17190115 A 20170908; AR P180102531 A 20180906; ES 17190115 T 20170908; FI 2018050639 W 20180910; HR P20240138 T 20170908; PL 17190115 T 20170908; RS P20240105 A 20170908