

Title (en)
FUEL INJECTION VALVE UNIT FOR AN INTERNAL COMBUSTION PISTON ENGINE AND A METHOD OF OPERATING THE FUEL INJECTION VALVE UNIT

Title (de)
KRAFTSTOFFEINSPRITZVENTILEINHEIT FÜR EINEN HUBKOLBENMOTOR UND VERFAHREN ZUM BETRIEB DER KRAFTSTOFFEINSPRITZVENTILEINHEIT

Title (fr)
UNITÉ DE SOUPAPE D'INJECTION DE CARBURANT POUR MOTEUR À PISTON À COMBUSTION INTERNE ET PROCÉDÉ D'EXPLOITATION DE LADITE UNITÉ

Publication
EP 3464874 A1 20190410 (EN)

Application
EP 16726619 A 20160525

Priority
FI 2016050358 W 20160525

Abstract (en)
[origin: WO2017203092A1] Invention relates to fuel injection valve unit (1) for an internal combustion piston engine, comprising a fuel inlet (9) connectable to a common rail system (40) of the internal combustion piston engine for feeding pressurized fuel into the valve unit (1); at least one fuel injection opening (8) arranged at an end of the valve unit (1) for controllably injecting fuel; a fuel space (6) with which the fuel inlet (9) is in flow communication; a control space (7) with which the fuel inlet (9) is flow communication; a control valve (5) arranged in connection with the control space (7), which control valve (5) is arranged to open or close a flow connection from the control space (7) to a discharge channel (10); a fuel injection valve needle (2,22) comprising a first end (3) and a second end (4), in which the first end of fuel injection valve needle (2,22) is arranged to open or close a flow communication between the fuel space (6) and the at least one fuel injection opening (8), and in which the second end (4) of the fuel injection valve needle (2,22) is arranged to extend into the control space (7); the fuel injection valve needle (2,22) is partially circumscribed by a cylindrical support section (12) arranged between the fuel space (6) and the control space (7) and through which the valve needle (2,22) is arranged to extend in supported manner into the control space (7); and wherein a contact area (14) between the cylindrical support section (12) and the valve needle (2,22) is provided with a grooving (13) arranged at least partially at an angle with the center axis (A) of the valve needle (2,22).

IPC 8 full level
F02M 61/18 (2006.01); **F02M 43/04** (2006.01); **F02M 47/02** (2006.01); **F02M 61/04** (2006.01)

CPC (source: EP)
F02M 45/08 (2013.01); **F02M 47/027** (2013.01); **F02M 61/042** (2013.01); **F02M 61/1893** (2013.01); **F02M 2200/40** (2013.01); **F02M 2200/44** (2013.01)

Citation (search report)
See references of WO 2017203092A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2017203092 A1 20171130; EP 3464874 A1 20190410; EP 3464874 B1 20201118

DOCDB simple family (application)
FI 2016050358 W 20160525; EP 16726619 A 20160525