

Title (en)  
PNEUMATIC SPINNING DEVICE, AND SPINNING MACHINE

Title (de)  
PNEUMATISCHE SPINNVORRICHTUNG UND SPINNMASCHINE

Title (fr)  
FILEUSE PNEUMATIQUE ET FILEUSE

Publication  
**EP 3470559 B1 20200415 (EN)**

Application  
**EP 18208991 A 20160602**

Priority  
• JP 2015134968 A 20150706  
• EP 16172580 A 20160602

Abstract (en)  
[origin: EP3115485A1] In a nozzle block (60), a first space (64), a second space (66), and a third space (67) are aligned from a first side toward a second side in a predetermined direction. The second space (66) is spread at a second inner surface tapered angle from the first side toward the second side. The third space (67) is spread at a third inner surface tapered angle greater than the second inner surface tapered angle from the first side toward the second side. A height (H1) of the first space (64) is a value greater than or equal to 3 mm and smaller than or equal to 8 mm. A height (H2) of the second space (66) is a value greater than or equal to 30% and smaller than or equal to 50% of a sum of the height (H2) and a height (H3) of the third space (67).

IPC 8 full level  
**D01H 1/115** (2006.01)

CPC (source: CN EP)  
**D01H 1/115** (2013.01 - CN EP); **D01H 4/02** (2013.01 - CN)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 3115485 A1 20170111**; **EP 3115485 B1 20190807**; CN 106400215 A 20170215; CN 106400215 B 20200512; EP 3470559 A1 20190417; EP 3470559 B1 20200415; JP 2017014672 A 20170119

DOCDB simple family (application)  
**EP 16172580 A 20160602**; CN 201610429426 A 20160616; EP 18208991 A 20160602; JP 2015134968 A 20150706