

Title (en)

STEEL SHEET FOR CROWN CAPS, PRODUCTION METHOD THEREFOR, AND CROWN CAP

Title (de)

STAHLBLECH FÜR KRONKORKEN, HERSTELLUNGSVERFAHREN DAFÜR UND KRONKORKEN

Title (fr)

TÔLE D'ACIER POUR CAPSULE-COURONNE, PROCÉDÉ DE FABRICATION CORRESPONDANT, ET CAPSULE-COURONNE

Publication

EP 3476964 B1 20210127 (EN)

Application

EP 17855743 A 20170914

Priority

- JP 2016192247 A 20160929
- JP 2017033179 W 20170914

Abstract (en)

[origin: EP3476964A1] To provide a steel sheet for crown caps, having sufficient pressure resistance and formability regardless of gauge reduction; a method for manufacturing the same; and a crown cap. A steel sheet for crown caps has a predetermined composition, wherein N total-(N as AlN) is 0.0090% to 0.0170%, the maximum grain size of a carbide is 2.0 μm or less in a cross section in a rolling direction, and the yield strength is 420 MPa to 600 MPa in the rolling direction. A method for manufacturing a steel sheet for crown caps includes a hot rolling step of coiling a steel material having a predetermined composition at a predetermined temperature after finish rolling; a primary cold rolling step; a continuous annealing step of performing heating at an average heating rate of 10 °C/s to 30 °C/s in a temperature range A from 500 °C to 600 °C in a heating course, annealing at an annealing temperature B in a temperature range from 620 °C to 740 °C, cooling from the annealing temperature B to a cooling stop temperature C in a temperature range from 400 °C to 580 °C at an average cooling rate of 20 °C/s or more, and retaining in the temperature range from 400 °C to 580 °C for a retention time of 30 seconds to 90 seconds after cooling at the above average cooling rate is stopped; and a secondary cold rolling step of performing cold rolling at a rolling reduction ratio of 1.0% to 12%.

IPC 8 full level

C21D 6/02 (2006.01); **B65D 41/10** (2006.01); **C21D 1/26** (2006.01); **C21D 1/28** (2006.01); **C21D 6/00** (2006.01); **C21D 8/02** (2006.01); **C21D 8/04** (2006.01); **C21D 9/46** (2006.01); **C22C 38/04** (2006.01); **C22C 38/06** (2006.01)

CPC (source: EP)

B65D 41/10 (2013.01); **C21D 1/26** (2013.01); **C21D 1/28** (2013.01); **C21D 6/005** (2013.01); **C21D 6/02** (2013.01); **C21D 8/0226** (2013.01); **C21D 8/0236** (2013.01); **C21D 8/0247** (2013.01); **C21D 8/0268** (2013.01); **C21D 9/46** (2013.01); **C22C 38/001** (2013.01); **C22C 38/04** (2013.01); **C22C 38/06** (2013.01)

Cited by

US12129535B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 3476964 A1 20190501; **EP 3476964 A4 20190522**; **EP 3476964 B1 20210127**; CO 2019001705 A2 20190308; JP 6601571 B2 20191106; JP WO2018061787 A1 20181220; MX 2019002404 A 20190620; MY 197920 A 20230725; PH 12019550011 A1 20191202; PL 3476964 T3 20210719; WO 2018061787 A1 20180405; ZA 201900744 B 20200826

DOCDB simple family (application)

EP 17855743 A 20170914; CO 2019001705 A 20190226; JP 2017033179 W 20170914; JP 2018542371 A 20170914; MX 2019002404 A 20170914; MY PI2019000961 A 20170914; PH 12019550011 A 20190123; PL 17855743 T 20170914; ZA 201900744 A 20190205