

Title (en)

BARREL HAVING A PRESSURE VALVE FOR STORING BEER, USE THEREOF, METHOD FOR CONTROLLING THE PRESSURE IN THE BARREL, BARREL HOLLOW FLOOR, MODULAR SYSTEM FOR PRODUCING A BARREL HOLLOW FLOOR AND METHOD FOR FILLING A BARREL

Title (de)

FASS MIT DRUCKVENTIL ZUM AUFBEWAHREN VON BIER, DESSEN VERWENDUNG, VERFAHREN ZUM REGELN DES DRUCKS IM FASS, FASSHOHLBODEN, MODULARES SYSTEM ZUM HERSTELLEN EINES FASSHOHLBODENS UND VERFAHREN ZUM BEFÜLLEN EINES FASSES

Title (fr)

FÛT COMPORTANT UNE SOUPEPE DE PRESSION POUR LA CONSERVATION DE BIÈRE, SON UTILISATION, PROCÉDÉ DE RÉGULATION DE LA PRESSION DANS LE FÛT, FOND DE FÛT CREUX, SYSTÈME MODULAIRE DE FABRICATION D'UN FOND DE FÛT CREUX ET PROCÉDÉ DE REMPLISSAGE D'UN FÛT

Publication

**EP 3500517 A1 20190626 (DE)**

Application

**EP 17777079 A 20170821**

Priority

- EP 16185057 A 20160820
- EP 16190516 A 20160926
- EP 17152529 A 20170120
- IB 2017055046 W 20170821

Abstract (en)

[origin: WO2018037332A2] The invention relates to a container, the contents of which can be removed easily by a consumer. The container should be inexpensive to produce while being extremely easy to operate by the consumer, should provide a high degree of flexibility with respect to the choice of propellant gas (pressure and type of gas) and should achieve a long shelf life for the contents, even after the container has been tapped. The container has a fill chamber (40), a pressure chamber (6) and a pressure valve (10). The fill chamber (40) is formed by a container base (2), a container wall (7) and a container upper face (8) and a first pressure (PB) prevails in the fill chamber (40). The pressure chamber (6) is formed by the container base (2) and a pressure chamber base (5), and a second pressure (PD) prevails in the pressure chamber (6). The pressure valve (10) is connected to the container base (2) and the pressure chamber base (5). The pressure valve (10), when open, fluidically connects the fill chamber (40) and the pressure chamber (6), and said pressure valve (10), when closed, fluidically seals off the fill chamber (40) from the pressure chamber (6).

IPC 8 full level

**B65D 83/14** (2006.01); **B65D 83/66** (2006.01); **B67D 1/04** (2006.01); **B67D 1/12** (2006.01)

CPC (source: EP US)

**B65D 83/14** (2013.01 - EP); **B65D 83/663** (2013.01 - EP US); **B67D 1/0437** (2013.01 - EP US); **B67D 1/0802** (2013.01 - US); **B67D 1/1252** (2013.01 - EP US); **B65D 83/14** (2013.01 - US); **B67D 2001/0824** (2013.01 - EP US)

Citation (search report)

See references of WO 2018037334A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**WO 2018037332 A2 20180301**; **WO 2018037332 A3 20180503**; AU 2017316746 A1 20190411; AU 2017316746 B2 20220210; BR 112019003230 A2 20190618; CA 3034506 A1 20180301; CN 109890747 A 20190614; CN 109890747 B 20220408; EP 3500516 A2 20190626; EP 3500516 B1 20210127; EP 3500517 A1 20190626; ES 2868678 T3 20211021; US 11597643 B2 20230307; US 2021206618 A1 20210708; WO 2018037334 A1 20180301

DOCDB simple family (application)

**IB 2017055044 W 20170821**; AU 2017316746 A 20170821; BR 112019003230 A 20170821; CA 3034506 A 20170821; CN 201780064776 A 20170821; EP 17772762 A 20170821; EP 17777079 A 20170821; ES 17772762 T 20170821; IB 2017055046 W 20170821; US 201716326631 A 20170821