

Title (en)
MACHINING DEVICE AND METHOD FOR MACHINING A ROTOR ARRANGED IN A TURBINE HOUSING WHICH CONSISTS OF TWO PARTS, THEREBY FORMING A JOINT, AND METHOD FOR REPAIRING AND/OR RETROFITTING A TURBINE

Title (de)
BEARBEITUNGSVORRICHTUNG UND VERFAHREN ZUR BEARBEITUNG EINES IN EINEM UNTER BILDUNG EINER TEILFUGE ZWEIGETEILTEN TURBINENGEHÄUSE ANGEORDNETEN ROTORS SOWIE VERFAHREN ZUR REPARATUR UND/ODER NACHRÜSTUNG EINER TURBINE

Title (fr)
DISPOSITIF ET PROCÉDÉ D'USINAGE DESTINÉS À L'USINAGE D'UN ROTOR DISPOSÉ DANS UN CARTER DE TURBINE EN DEUX PARTIES POUR FORMER UN JOINT DE SÉPARATION AINSI QUE PROCÉDÉ DE RÉPARATION ET/OU DE MISE À NIVEAU D'UNE TURBINE

Publication
EP 3509788 A1 20190717 (DE)

Application
EP 17752352 A 20170808

Priority
• DE 102016216857 A 20160906
• EP 2017069994 W 20170808

Abstract (en)
[origin: WO2018046209A1] The invention relates to a machining device (13) for machining a rotor arranged in a turbine housing which consists of two parts, thereby forming a joint (11), in situ while the upper housing half is removed, comprising the following: - a main part (14) which has securing means (21) for releasably securing the main part (14) to the lower housing half (12) in the region of the joint (11), at least one tool holder (15) for receiving at least one machining tool (24) which is secured on the main part (14) directly or indirectly so as to be alignable relative to the main part (14), - multiple telescopic stabilizing elements (16) which can be locked into different longitudinal settings preferably in a continuous manner, the free end of each of which is secured to the main part (14) in an articulated manner, and the other free ends of which are provided with additional securing means (49) that are designed such that the free ends can be secured to the lower housing half (12) of the turbine housing in a releasable and articulated manner. The invention additionally relates to a method for machining a rotor arranged in a turbine housing which consists of two parts, thereby forming a joint (11), and to a method for repairing and/or retrofitting a turbine.

IPC 8 full level
B23Q 9/00 (2006.01); **B23P 6/00** (2006.01); **B23Q 11/00** (2006.01); **F01D 5/00** (2006.01); **F01D 25/28** (2006.01)

CPC (source: EP KR US)
B23P 6/002 (2013.01 - KR US); **B23Q 9/0042** (2013.01 - EP KR US); **B23Q 11/001** (2013.01 - EP US); **B23Q 11/0032** (2013.01 - EP KR US); **B23Q 11/0046** (2013.01 - US); **F01D 5/3007** (2013.01 - EP KR US); **F01D 25/24** (2013.01 - KR); **F01D 25/285** (2013.01 - KR); **F01D 25/24** (2013.01 - EP US); **F01D 25/285** (2013.01 - EP US); **G01B 11/02** (2013.01 - US); **G01B 11/22** (2013.01 - US)

Citation (search report)
See references of WO 2018046209A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
DE 102016216857 A1 20180308; EP 3509788 A1 20190717; EP 3509788 B1 20221026; ES 2935645 T3 20230308; KR 102229550 B1 20210318; KR 20190045285 A 20190502; US 11000929 B2 20210511; US 2019184510 A1 20190620; WO 2018046209 A1 20180315

DOCDB simple family (application)
DE 102016216857 A 20160906; EP 17752352 A 20170808; EP 2017069994 W 20170808; ES 17752352 T 20170808; KR 20197009425 A 20170808; US 201716330150 A 20170808