

Title (en)  
CASE

Title (de)  
GEHÄUSE

Title (fr)  
BOÎTIER

Publication  
**EP 3511059 B1 20230920 (EN)**

Application  
**EP 18214001 A 20181219**

Priority  
JP 2018005191 A 20180116

Abstract (en)  
[origin: EP3511059A1] This case is a case configured to accommodate a controller, the controller including: a first main surface; a second main surface provided on a side opposite to the first main surface; a first side surface and a second side surface provided on both ends in a longer direction of the first main surface and the second main surface; and a first side end surface and a second side end surface provided on both ends in a shorter direction of the first main surface and the second main surface. The controller further includes: a first operation portion provided on the first main surface; a second operation portion provided on the first end surface; a third operation portion provided on the second main surface; and an image capturing section provided on the second end surface. The case includes: a case main body portion having an accommodating space in which the controller can be accommodated; and at least one protruding portion protruding from the case main body portion. The case main body portion is formed into a lengthwise shape including: a first end portion corresponding to the first end surface of the controller when the controller is accommodated in the accommodating space; and a second end portion corresponding to the second end surface of the controller when the controller is accommodated in the accommodating space. The case main body portion is provided with: a first opening portion that is provided on the second end portion side and is for allowing image capture of the outside of the case main body portion by the image capturing section when the controller is accommodated in the accommodating space; a second opening portion from which at least part of the first operation portion is exposed when the controller is accommodated in the accommodating space; and a third opening portion from which at least part of the third operation portion is exposed when the controller is accommodated in the accommodating space. The protruding portion is disposed on the first end portion side with respect to the third opening portion.

IPC 8 full level  
**A63F 13/24** (2014.01); **A63F 13/98** (2014.01)

CPC (source: EP US)  
**A63F 13/24** (2014.09 - EP US); **A63F 13/98** (2014.09 - EP US)

Citation (examination)

- US 9462865 B2 20161011 - TAKAYAMA STEVEN RYUTARO [US], et al
- EP 3103532 A2 20161214 - NINTENDO CO LTD [JP]

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**EP 3511059 A1 20190717**; **EP 3511059 B1 20230920**; JP 2019122569 A 20190725; JP 6703015 B2 20200603; US 10857471 B2 20201208; US 2019217208 A1 20190718

DOCDB simple family (application)  
**EP 18214001 A 20181219**; JP 2018005191 A 20180116; US 201816224095 A 20181218