

Title (en)

FIRE DETECTOR BASE AND FIRE DETECTOR

Title (de)

BASIS FÜR BRANDSENSOR UND BRANDSENSOR

Title (fr)

BASE POUR CAPTEUR D'INCENDIE ET CAPTEUR D'INCENDIE

Publication

**EP 3514774 B1 20230712 (EN)**

Application

**EP 17850699 A 20170831**

Priority

- JP 2016182336 A 20160916
- JP 2017031291 W 20170831

Abstract (en)

[origin: EP3514774A1] An object of the present invention is to provide a fire detector base and a fire detector, which can reduce a space to be needed for connecting an internal terminal and an external connection terminal. Respective internal terminals (60) correspond to external connection terminals (50) in one-to-one. Each of the internal terminals (60) is electrically connected to a target external connection terminal (50) that is one corresponding to each internal terminal (60) noted, of the external connection terminals (50). In each of the internal terminals (60), a distance from each internal terminal (60) noted to the target external connection terminal (50) is shorter than a distance from the each internal terminal (60) noted to any other one of the internal terminals (60), and shorter than a distance from the target external connection terminal (50) to any other one of the external connection terminals (50).

IPC 8 full level

**G08B 17/113** (2006.01)

CPC (source: EP)

**G08B 17/113** (2013.01)

Citation (examination)

JP 2008027349 A 20080207 - MATSUSHITA ELECTRIC WORKS LTD

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 3514774 A1 20190724; EP 3514774 A4 20190911; EP 3514774 B1 20230712;** JP WO2018051796 A1 20190704;  
WO 2018051796 A1 20180322

DOCDB simple family (application)

**EP 17850699 A 20170831;** JP 2017031291 W 20170831; JP 2018539621 A 20170831