

Title (en)
PROFILED PLASTIC SECTION FOR A METAL/PLASTIC COMPOSITE PROFILED SECTION

Title (de)
KUNSTSTOFFPROFIL FÜR EIN METALL-KUNSTSTOFF-VERBUNDPROFIL

Title (fr)
PROFILÉ EN PLASTIQUE POUR UN PROFILÉ COMPOSITE EN MÉTAL ET PLASTIQUE

Publication
EP 3526434 B1 20201209 (DE)

Application
EP 17797737 A 20171012

Priority
• DE 102016119580 A 20161013
• IB 2017056315 W 20171012

Abstract (en)
[origin: WO2018069859A1] The invention relates to a profiled plastic section (1) for a metal/plastic composite profiled section (31). The profiled plastic section (1) comprises a first profiled element (2) and at least one second profiled element (3). The first profiled element (2) and the second profiled element (3) together form a latching mechanism (4, 9; 5, 10; 6, 11), by means of which a form-fitting connection can preferably be produced between the first profiled element (2) and the second profiled element (3) in a width direction (x) and in a height direction (y). The first profiled element (2) and the second profiled element (3) overlap preferably over a large area when the form-fitting connection is produced between the first profiled element (2) and the second profiled element (3), and the form-fitting connection can be produced on the cross-sectional plane (x, y) between the first profiled element (2) and the second profiled element (3) by latching the profiled elements (2, 3) of the profiled plastic section (1). The form-fitting connection between the first profiled element (2) and the second profiled element (3) is designed such that a movement of the first profiled element (2) and the second profiled element (3) in a longitudinal direction (z) of the profiled plastic section (1) is allowed when a first metal component (29) is connected to the first profiled element (2) and a second metal component (30) is connected to the second profiled element (3) preferably in a shear-resistant manner. The profiled plastic section (1) can likewise also be designed with more than two profiled elements (2, 3), and the basic principle according to the invention of generating a shear-free plastic/metal composite profiled section (31) can be carried over.

IPC 8 full level
E06B 3/273 (2006.01); **E06B 3/263** (2006.01)

CPC (source: EP US)
E06B 1/18 (2013.01 - US); **E06B 1/28** (2013.01 - US); **E06B 1/30** (2013.01 - US); **E06B 3/26303** (2013.01 - EP US); **E06B 3/26305** (2013.01 - EP); **E06B 3/2632** (2013.01 - US); **E06B 3/273** (2013.01 - EP); **E06B 2003/26312** (2013.01 - US); **E06B 2003/26316** (2013.01 - EP US); **E06B 2003/26329** (2013.01 - US); **E06B 2003/2633** (2013.01 - EP); **E06B 2003/26352** (2013.01 - EP); **E06B 2003/26379** (2013.01 - EP)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2018069859 A1 20180419; CN 109844251 A 20190604; CN 109844251 B 20210709; DE 102016119580 A1 20180419; EP 3526434 A1 20190821; EP 3526434 B1 20201209; ES 2857714 T3 20210929; US 11414917 B2 20220816; US 11873674 B2 20240116; US 2020040640 A1 20200206; US 2022333432 A1 20221020

DOCDB simple family (application)
IB 2017056315 W 20171012; CN 201780063608 A 20171012; DE 102016119580 A 20161013; EP 17797737 A 20171012; ES 17797737 T 20171012; US 201716338979 A 20171012; US 202217858534 A 20220706